

## Synergy™

### double pole switches - white



7 301 10



7 300 22

Front plates: white thermoset  
Terminal screws captive and backed off ready for cabling - large angled terminal entries  
Compact mechanism for maximised wiring space  
Supplied with faceplate screw caps

Pack	Cat.Nos	Double pole switches 20 A - 250 V~
10	7 300 10	Conform to BS EN 60669-1 For flush-mounting, back box to be min. 25 mm deep Use cord outlet accessory box Cat.No 7 300 53 for external cord outlet ASTA licence Nominal plate dimensions: 86 x 86 mm DP switch 
10	7 300 12	DP switch + red LED power indicator LED invisible until activated 
10	7 301 10	DP switch marked "WATER HEATER" 
10	7 301 12	DP switch marked "WATER HEATER" + red LED power indicator LED invisible until activated 

Pack	Cat.Nos	Double pole switches 45 A - 250 V~
10	7 300 22	Conform to BS EN 60669-1 ASTA licence For flush-mounting, back box to be min. 45 mm deep <b>Nominal plate dimensions: 86 x 86 mm</b> DP switch 
10	7 300 23	DP switch + red LED power indicator LED invisible until activated 
10	7 301 22	DP switch red rocker marked "COOKER" 
5	7 300 20	<b>Nominal plate dimensions: 146 x 86 mm</b> DP switch 
5	7 300 21	DP switch + red LED power indicator LED invisible until activated 
5	7 301 20	DP switch red rocker marked "COOKER" 

## Synergy™

### telephone and data sockets - white



7 300 50



7 300 57

Front plates: white thermoset  
Terminal screws captive and backed off ready for cabling - large angled terminal entries  
Compact mechanism for maximised wiring space  
Supplied with faceplate screw caps

Pack	Cat.Nos	Euro module front plates
10	7 300 99	Suitable for use with standard 25 x 50 mm Euro data module inserts 1 gang - 86 x 86 mm 2 modules - aperture size 50 x 50 mm 
10	7 301 00	2 gang - 86 x 146 mm 4 modules - aperture size 50 x 100 mm 
10	7 300 50	<b>Telephone sockets</b> For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm UK master 
10	7 300 51	UK secondary
10	7 300 54	RJ 11/RJ 12 - single
1	7 300 56	<b>Data sockets - Cat. 6</b> Rapid cable connection For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm RJ 45 - single 
1	7 300 57	RJ 45 - twin 