



6 781 33



6 781 38



7 300 89



7 300 69

Front plates: white thermoset  
Terminal screws captive and backed off ready for cabling - large angled terminal entries  
Compact mechanism for maximised wiring space  
Supplied with faceplate screw caps


Pack	Cat.Nos	<b>Double pole socket outlets 13 A - 250 V<math>\sim</math> (continued)</b>
10	7 300 64	Conform to BS 1363: Part. 2 With safety shutter mechanism For flush-mounting, back box to be min. 25 mm deep ASTA licence <b>Switched for standard and clean earth applications</b> 1 gang Nominal plate dimensions: 86 x 86 mm
5	7 300 74	2 gang Nominal plate dimensions: 86 x 146 mm
10	7 301 62	<b>Switched with red rocker</b> 1 gang Nominal plate dimensions: 86 x 86 mm
5	7 301 61	2 gang Nominal plate dimensions: 86 x 146 mm

Pack	Cat.Nos	<b>RCD sockets 13 A - 250 V<math>\sim</math></b>
1	6 781 33	Conform to BS 7288: 1990 and BS 1363 - Part 2: 1995 Conventional earth pin release shutter Maximum operating current 16 A Electronic RCD module with a membrane switch for "test and reset" Flush mounting back box : min. 25 mm deep <b>ELO - DP 30 mA</b> Trips in the event of a power failure Ideal for applications where it is desirable to prevent automatic reactivation of equipment after a power failure For hazardous, e.g. machinery, power tools 1 gang Nominal plate dimensions: 86 x 86 mm
1	6 781 37	2 gang Nominal plate dimensions: 86 x 146 mm
1	6 781 34	<b>ELR - DP 30 mA</b> Trips in the event of a power failure Ideal for applications where it is desirable to automatically re-activate equipment after a power failure E.g. fridge, freezer, unmanned areas 1 gang Nominal plate dimensions: 86 x 86 mm
1	6 781 38	2 gang Nominal plate dimensions: 86 x 146 mm

Pack	Cat.Nos	<b>Socket outlets 15 A - 250 V<math>\sim</math></b>
10	7 300 88	Conform to BS 546 Patented 3 pin safety shutter mechanism For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm 1 gang - unswitched
10	7 300 89	1 gang - switched, single pole
5	7 300 85	<b>Socket outlets 15 A - 127 V<math>\sim</math></b> Standard terminal screws For flush-mounting, back box to be min. 35 mm deep 1 gang unswitched Nominal plate dimensions: 86 x 86 mm
5	7 300 86	2 gang unswitched Nominal plate dimensions: 86 x 146 mm

Pack	Cat.Nos	<b>Socket outlets 5 A - 250 V<math>\sim</math></b>
10	7 300 68	Conform to BS 546 Patented 3 pin safety shutter mechanism For flush-mounting, back box to be min. 25 mm deep Nominal plate dimensions: 86 x 86 mm 1 gang - unswitched
10	7 300 69	1 gang - switched, single pole
10	7 300 59	<b>Socket outlet 2 A - 250 V<math>\sim</math></b> Conform to BS 546 For flush-mounting, back box to be min. 25 mm deep Nominal plate dimensions: 86 x 86 mm 1 gang - unswitched

British standard multi-outlet extensions, **p. 611**



BS plugs, **p. 609**

