

Synergy™

TV sockets - white



7 300 43

Technical characteristics [see e-catalogue](#)

For DVBT, Cablecast and satellite installation
 UHD TV compatible
 Class A shielded star sockets LTE Ready (4G protected)
 Recommended coaxial cable: 17 VATC
 Star cabling (1 socket = 1 cable to antenna, splitter or multiswitch)
 Visual checking of the connection
 Meet EN 50083-4 and EN 50083-2 European directive
 TV: male connector (Ø9.5 mm)
 R: female connector (Ø9.5 mm)
 SAT: "F type" connector
 TV: 5-68 / 120-862 MHz
 R: 87.5-108 MHz
 SAT: 950-2400 MHz
 2 modules

Pack Cat.Nos Multi TV star sockets

1	7 301 41 <small>AVAILABLE SEPT 2016</small>	TV-SAT Low attenuation: < 1 dB
1	7 300 43	TV-R-SAT Low attenuation: < 1.5 dB

Single TV star sockets

10	7 300 40	TV 9.5 mm male
1	7 300 41	TV "F" type

Other TV sockets

10	7 301 40	Installation in case of maintenance An amplifier and a line balancing are recommended Single - female
10	7 301 44	Single passthrough - female
10	7 301 45	Single terminal - female

Synergy™

British standard socket outlets - white



7 300 65



7 300 60



7 300 70

Front plates: white thermoset
 Terminal screws captive and backed off ready for cabling - large angled terminal entries
 Compact mechanism for maximised wiring space
 Supplied with faceplate screw caps

Pack	Cat.Nos	Socket outlets 13 A - 250 V~
		Conform to BS 1363: Part. 2 For flush-mounting, back box to be min. 25 mm deep With safety shutter mechanism ASTA licence
10	7 300 65	Unswitched 1 gang Nominal plate dimensions: 86 x 86 mm
5	7 300 75	2 gang Nominal plate dimensions: 86 x 146 mm
10	7 300 66	Single pole - switched 1 gang Nominal plate dimensions: 86 x 86 mm
5	7 300 76	2 gang Nominal plate dimensions: 86 x 146 mm
		Socket outlets 13 A - 250 V~ Special earth pin With safety shutter mechanism For flush-mounting, back box to be min. 25 mm deep
10	7 300 67	Double pole - switched 1 gang Nominal plate dimensions: 86 x 86 mm
5	7 300 77	2 gang Nominal plate dimensions: 86 x 146 mm
		Double pole socket outlets 13 A - 250 V~ Conform to BS 1363: Part. 2 With safety shutter mechanism For flush-mounting, back box to be min. 25 mm deep ASTA licence
10	7 300 60	Switched 1 gang Nominal plate dimensions: 86 x 86 mm
5	7 300 70	2 gang Nominal plate dimensions: 86 x 146 mm
10	7 300 61	Switched with red LED power indicator LED invisible until activated 1 gang Nominal plate dimensions: 86 x 86 mm
5	7 300 71	2 gang Nominal plate dimensions: 86 x 146 mm