



Front plates: grey epoxy coated steel
Terminal screws captive and backed off ready for cabling - large angled terminal entries
Supplied complete with close fit 43 mm deep surface-mounting back box

Pack	Cat.Nos	Single pole plate switches 10 AX - 250 V~	Pack	Cat.Nos	Television sockets
5	7 338 00	Conform to BS EN 60669-1: 2000 Flush-mounting back box: min. 16 mm deep Nominal plate dimensions: 86 x 86 mm 1 gang - 1-way	5	7 338 40	Flush-mounting back box: min. 35 mm deep Nominal plate dimensions: 86 x 86 mm Screened TV - single, male
5	7 338 01		1	7 338 41	Screened satellite - single, "F" type
5	7 338 05		1 gang - 2-way		
5	7 338 02	1 gang - intermediate			
5	7 338 02	2 gang - 2-way			
5	7 338 03	3 gang - 2-way			
		Double pole switches 20 A - 250 V~			Telephone sockets
5	7 338 10	Conform to BS EN 60669-1: 2000 Flush-mounting back box: min. 25 mm deep Nominal plate dimensions: 86 x 86 mm DP switch	5	7 338 50	Flush-mounting back box: min. 35 mm deep Nominal plate dimensions: 86 x 86 mm Single master
5	7 338 16	DP switch with cord outlet + red LED power indicator	5	7 338 51	Single secondary
5	7 338 12	DP switch + red LED power indicator			
		Double pole switch 45 A - 250 V~			Data sockets Cat. 6
5	7 338 21	Conforms to BS EN 60669-1: 2000 Red rocker Flush-mounting back box: min. 48 mm deep Nominal plate dimensions: 146 x 86 mm DP switch + red power indicator	1	7 338 56	Rapid cable connection Flush-mounting back box: min. 35 mm deep Nominal plate dimensions: 86 x 86 mm RJ 45 - single
			1	7 338 57	RJ 45 - twin
					Blanking plates
			5	7 338 95	1 gang Nominal plate dimensions: 86 x 86 mm
			5	7 338 96	2 gang Nominal plate dimensions: 86 x 146 mm
					Cable outlet 20 A - 250 V~
			5	7 338 19	Conforms to BS 5733: 1995 Flush-mounting back box: min. 25 mm deep Nominal plate dimensions: 86 x 86 mm 20 A - with terminal block and outlet gland