



8 321 31



8 323 32



8 325 33



8 321 51



8 323 57



8 325 50

Sleek design

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

GG: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos	Single pole plate switches 10 AX - 250 V~
		Conform to BS EN 60669-1 For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm
1	8 320 01	1 gang - 2-way switches ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 01	
1	8 324 01	
1	8 320 02	2 gang - 2-way switches ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 02	
1	8 324 02	

Pack	Cat.Nos	Single pole plate switches 20 AX - 250 V~
		Conform to BS EN 60669-1 For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm
1	8 321 31	1 gang - 2-way switches ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 323 31	
1	8 325 31	
1	8 321 32	2 gang - 2-way switches Nominal plate dimensions: 86 x 86 mm ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 323 32	
1	8 325 32	
1	8 321 33	3 gang - 2-way switches Nominal plate dimensions: 86 x 86 mm ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 323 33	
1	8 325 33	
1	8 321 34	4 gang - 2-way switches Nominal plate dimensions: 86 x 146 mm ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 323 34	
1	8 325 34	

Pack	Cat.Nos	Single pole intermediate 10 AX - 250 V~
		Conform to BS EN 60669-1 For flush-mounting, back box to be min. 35 mm deep
1	8 320 05	● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 05	
1	8 324 05	

Pack	Cat.Nos	Single pole push switches 10 A - 250 V~
		Conform to BS EN 60669-1 For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm
1	8 320 07	● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 07	
1	8 324 07	

Pack	Cat.Nos	Push on/off rotary universal dimmers 5 W/300 W 100 - 240 V~ - 50/60 Hz
		Conform to IEC 60669-2-1 For flush-mounting back box to be min. 40 mm deep Equipped with overvoltage and short-circuit protection Screw terminals For all types of lamps: - dimmable LEDs: 5 W to 75 W - dimmable compact fluorescent lamps: 5 W to 75 W - halogen with ferromagnetic or electronic transformer: 5 VA to 300 VA - fluorescent tube - ballast: 5 VA to 300 VA - halogen and incandescent 230 V: 5 W to 300 W When switched on, gradually (2 seconds) lights up at the level set before last switch-off Nominal plate dimensions: 86 x 86 mm
1	8 321 51	1 gang - 2-way push switches ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 323 51	
1	8 325 51	

Pack	Cat.Nos	Push on/off rotary dimmers 400 W 100 - 240 V~ - 50/60 Hz
		Conform to BS EN 60669-1 For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm
1	8 321 56	1 gang - 2 way ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 323 56	
1	8 325 56	
1	8 321 57	2 gang - 2 way ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 323 57	
1	8 325 57	

Pack	Cat.Nos	Push on/off rotary dimmers 1000 W 250 V~ - 50/60 Hz
		Conform to BS EN 60669-1 - For flush-mounting back box to be min. 40 mm deep - 60-1000 W (230 V) - 60-500 W(127 V) for incandescent and halogen lamps 60-600 VA (230 V) - 60-300 VA (127 V) for halogen lamps with electronic transformers 60-100 VA (230 V) - 60-500 VA (127 V) for halogen lamps with ferromagnetic transformers Nominal plate dimensions: 86 x 86 mm
1	8 321 50	1 gang - 2-way push switches ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 323 50	
1	8 325 50	