

Synergy™ - telephone, data sockets and television sockets - Sleek Design



8 320 50

8 324 57

8 322 41

Sleek design

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

GG: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos	Telephone sockets
		For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm
1	8 320 50	UK master <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 50	
1	8 324 50	
1	8 320 51	UK secondary <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 51	
1	8 324 51	
1	8 320 54	RJ 11 / RJ 12 - single <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 54	
1	8 324 54	
		Data sockets Cat. 6
		Rapid cable connection For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm
1	8 320 56	RJ 45 - single <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 56	
1	8 324 56	
1	8 320 57	RJ 45 - twin <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 57	
1	8 324 57	
		Television sockets
		For flush-mounting, back box to be min. 35 mm deep Screened Nominal plate dimensions: 86 x 86 mm
1	8 320 40	TV sockets - single male <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 40	
1	8 324 40	
1	8 320 41	SAT sockets - single "F" type <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 41	
1	8 324 41	
1	8 320 43	TV-R-SAT sockets - "F" type <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 43	
1	8 324 43	

Synergy™ - cooker control units, fused connection units and cable outlets - Sleek Design



8 320 32

8 322 37

8 324 19

Sleek design

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

GG: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos	Cooker control units - 250 V~
		Conform to BS 4177: 1992. For flush-mounting, back box to be min 47 mm deep Nominal plate dimensions: 86 x 146 mm
1	8 320 29	45 A DP switch + 13 A DP switched socket outlet - with blue LED power indicator <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 29	
1	8 324 29	
		Fused connection units unswitched 13 A - 250 V~
		Conform to BS 1363: Part. 4. Front cable outlet with cord grip. Fuses supplied. Locked captive fuse carrier (padlockable). For flush-mounting, back box to be min. 35 mm deep. Supplied with 1 gang side extension Cat.No 8 321 98 (3 mm thick) in case of extra wiring space needed Nominal plate dimensions: 86 x 86 mm
1	8 320 32	Unswitched - with cord outlet <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 32	
1	8 324 32	
		Fused connection units switched 13 A - 250 V~
		Conform to BS 1363: Part. 4. Front cable outlet with cord grip. Fuses supplied. Locked captive fuse carrier (padlockable). For flush-mounting, back box to be min. 35 mm deep. Supplied with 1 gang side extension Cat.No 8 321 98 (3 mm thick) in case of extra wiring space needed Nominal plate dimensions: 86 x 86 mm
1	8 320 35	DP switched - without cord outlet <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 35	
1	8 324 35	
1	8 320 37	DP switched - with blue LED power indicator + cord outlet <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 37	
1	8 324 37	
		Cable outlets
		Conform to BS 5733. Fitted with clamp and outlet membrane. With terminal block Nominal plate dimensions: 86 x 86 mm
1	8 320 19	20 A - 250 V~ <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 19	
1	8 324 19	
1	8 320 26	45 A - 250 V~ <ul style="list-style-type: none"> ● Anthracite grey colour (plastic)