



8 320 75



8 322 61



8 324 89



8 322 59



8 320 44

Sleek design

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

GG: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos	Socket outlets 13 A - 250 V~
		Conform to BS EN 1363: Part. 2 With safety shutter mechanism For flush-mounting, back box to be min. 35 mm deep ASTA licence
		1 gang unswitched Nominal plate dimensions: 86 x 86 mm
1	8 320 65	● Brushed stainless steel
1	8 322 65	● Polished stainless steel
1	8 324 65	● Glossy gold
		2 gang unswitched Nominal plate dimensions: 86 x 146 mm
1	8 320 75	● Brushed stainless steel
1	8 322 75	● Polished stainless steel
1	8 324 75	● Glossy gold

Pack	Cat.Nos	Single pole socket outlets 13 A - 250 V~
		Conform to BS EN 1363: Part. 2 With safety shutter mechanism For flush-mounting, back box to be min. 35 mm deep
		1 gang switched Nominal plate dimensions: 86 x 86 mm
1	8 320 66	● Brushed stainless steel
1	8 322 66	● Polished stainless steel
1	8 324 66	● Glossy gold
		1 gang switched with blue LED power indicator Nominal plate dimensions: 86 x 86 mm
1	8 320 67	● Brushed stainless steel
1	8 322 67	● Polished stainless steel
1	8 324 67	● Glossy gold
		2 gang switched Nominal plate dimensions: 86 x 146 mm
1	8 320 76	● Brushed stainless steel
1	8 322 76	● Polished stainless steel
1	8 324 76	● Glossy gold
		2 gang switched with blue LED power indicator Nominal plate dimensions: 86 x 146 mm
1	8 320 77	● Brushed stainless steel
1	8 322 77	● Polished stainless steel
1	8 324 77	● Glossy gold

Pack	Cat.Nos	Double pole socket outlets 13 A - 250 V~
		Conform to BS EN 1363: Part. 2 With safety shutter mechanism For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm ASTA licence
		1 gang switched
1	8 320 60	● Brushed stainless steel
1	8 322 60	● Polished stainless steel
1	8 324 60	● Glossy gold
		1 gang switched with blue LED power indicator
1	8 320 61	● Brushed stainless steel
1	8 322 61	● Polished stainless steel
1	8 324 61	● Glossy gold

Pack	Cat.Nos	Double pole socket outlets 13 A - 250 V~ (continued)
		Conform to BS EN 1363: Part. 2 With safety shutter mechanism For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 146 mm ASTA licence
		2 gang switched
1	8 320 70	● Brushed stainless steel
1	8 322 70	● Polished stainless steel
1	8 324 70	● Glossy gold
		2 gang switched with blue LED power indicator
1	8 320 71	● Brushed stainless steel
1	8 322 71	● Polished stainless steel
1	8 324 71	● Glossy gold

Pack	Cat.Nos	Socket outlets 15 A - 250 V~
		Conform to BS 546 Patented 3 pin safety shutter mechanism For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm
		1 gang switched
1	8 320 89	● Brushed stainless steel
1	8 322 89	● Polished stainless steel
1	8 324 89	● Glossy gold

Pack	Cat.Nos	Socket outlets 5 A - 250 V~
		Conform to BS 546 Patented 3 pin safety shutter mechanism For flush-mounting, back box to be min. 25 mm deep Nominal plate dimensions: 86 x 86 mm
		1 gang switched - single pole
1	8 320 69	● Brushed stainless steel
1	8 322 69	● Polished stainless steel
1	8 324 69	● Glossy gold

Pack	Cat.Nos	Socket outlets 2 A - 250 V~
		Conform to BS 546 For flush-mounting, back box to be min. 25 mm deep Nominal plate dimensions: 86 x 86 mm
		1 gang unswitched
1	8 320 59	● Brushed stainless steel
1	8 322 59	● Polished stainless steel
1	8 324 59	● Glossy gold

Pack	Cat.Nos	Double USB socket
		Conform to IEC 62684 For flush-mounting, back box to be min. 40 mm deep Input voltage: 110 V/ 230 V 5 V (output) - 2400 mA. Wiring with 1.5 mm ² and 2.5 mm ² (only live and neutral)
		1 gang unswitched
1	8 320 44	● Brushed stainless steel
1	8 322 44	● Polished stainless steel
1	8 324 44	● Glossy gold