

# Plexo<sup>3</sup>

## IP 65 weatherproof cabinets, multifunction sleeves and accessories



Technical characteristics **p. 261**

Self-extinguishing: resistance to incandescent wire 650°C  
 Conform to EN 60439-3  
 Weatherproof cabinets - IP 65 - IK 09 - Class II  
 Door and cabinet fully reversible  
 Removable chassis and faceplates from 2-row versions up  
 2-position rail for modular products and moulded cases  
 Spacing between rails 150 mm  
 Can be fitted with perforated plates and solid faceplates for mounting non-modular products  
 Lockable door handle, sealable cover and faceplate  
 Shock-resistant polystyrene material  
 Box colour light grey L750A, cover colour dark grey R746A  
 Supplied without terminal blocks

Pack	Cat.Nos	<b>Cabinets 2 to 8 modules</b>	
		Number of rows	Number of modules
6	6 019 32	1	2 (+1)
6	6 019 94	1	4
6	6 019 96	1	6
6	6 019 98	1	8

Pack	Cat.Nos	<b>Cabinets 12 modules per row</b>	
		Number of rows	
1	6 018 31	1	
1	6 018 32	2	
1	6 018 33	3	

Pack	Cat.Nos	<b>Cabinets 18 modules per row</b>	
		Number of rows	
1	6 018 35	1	
1	6 018 36	2	
1	6 018 37	3	
1	6 018 38	4	

Pack	Cat.Nos	<b>Multifunction sleeves</b>	
		Supplied with hinges connecting the cover to the back of the cabinet	
		For use with 12 and 18-module cabinets using joining kit Cat.No 0 019 67	
		Can be fitted with control units and accessories: P17 16 A and 32 A sockets with standard fixing centres, flush-mounted IP 55 Plexo wiring accessories, Osmoz, modular rail at the back of the box	
		<b>Vertical</b>	
1	0 019 17	For 2 rows cabinets	
1	0 019 18	For 3 rows cabinets	

Pack	Cat.Nos	<b>Accessories</b>	
5	0 019 71	<b>Plexo adaptor</b> For fixing Plexo flush mounting wiring accessories, complete version (p. 592) on Plexo <sup>3</sup> cabinets (minimum 2 rows)	
		<b>Installation supports for terminal blocks</b> Set of 2 supports for mounting additional terminal blocks (p. 190) or empty supports for screw terminal blocks (p. 190) into Plexo <sup>3</sup> cabinets	
1	0 019 72	For 1 and 2 rows cabinets, 12 and 18 modules per row	
1	0 019 73	For 3 and 4 rows cabinets, 12 and 18 modules per row	
1	0 019 66	<b>Key lock</b> N° 850	
1	0 019 67	<b>Joining kit</b> Allows cables to be run horizontally or vertically between 2 cabinets or multifunction sleeves while maintaining IP 65 protection	
1	0 019 68	<b>Sealing kit</b> Set of 2 sealable terminal shields for cover and 8 sealable supports for faceplate	
1	0 019 69	<b>Fixing lugs</b> Set of 4 wall mounting lugs	
20	0 019 61	<b>Blanking plates</b> 5, separable into modules or 1/2 module Grey R746A	
1	0 019 55	<b>Direct piercing end caps</b> Pack consisting of 2 Ø32 mm ISO end caps, 5 Ø25 mm ISO end caps and 10 Ø20 mm ISO end caps	
2	0 019 64	<b>Plain faceplates</b> For 12 modules cabinets	
2	0 019 65	For 18 modules cabinets	
		<b>Perforated plates</b> Allow the DIN rail to be replaced with a LINA 25 plate when integrating non-modular products	
2	0 019 62	For 12 modules cabinets, Height 150 mm	
2	4 018 53	For 18 modules cabinets, Height 150 mm	
2	0 019 70	<b>Hinges</b> Set of 2 hinges connecting the back of the cabinet to the cover	