



### More Switchsocket Outlets...

K2946ALM  
K2946D5 ALM  
K2946D6ALM  
K2977D5 ALM  
K2977D6 ALM

## K2977 ALM

### 1 GANG DP WITH DUAL EARTH TERMINALS

STANDARD CARTON QUANTITY: 5

Earth terminal fitted in boxes.

DIMENSIONS:  
1 gang : 86 x 86 x 51mm

TERMINAL CAPACITY :  
2 x 6mm<sup>2</sup> stranded (max)

KNOCKOUTS:  
1 gang : 6 x 20mm.  
Two in one side and one in each of the other three sides. One in base

SPARE BOXES:  
1 gang : K829 ALM\* K899 ALM

All boxes have a base knockout.

Boxes: BS 5733 : 1995  
Socket: BS 1363 Pt.2: 1995

#### High integrity earthing

One gang switchsockets,two gang outboard switchsockets and two gang unswitched sockets are fitted with two earth terminals to provide a double earth facility for use when installations require a high integrity protective connection as specified within BS 7671 : 2008 .

#### Double pole switching

All switchsockets have double pole switching (neutral makes first,breaks last).

BS 1363 Pt.2: 1995  
Socket: BS 1363 Pt.2: 1995

### Downloads:

[Technical Specification](#)

[Full Range Information](#)

[Abbreviations](#)



### Order Literature

[Copy Text](#)