

Cooker Connection Unit

FLUSH



K5045WHI

Cooker Controls

45 AMP
MOULDED
FLUSH



K5060WHI



K5061WHI

45 AMP
MOULDED
SURFACE



K5040WHI




K5041WHI

45 AMP
METAL
FLUSH



K5011WHI

45 AMP
METAL
SURFACE



K5001WHI

K5045WHI**10****K5060WHI**

45A
DP MAIN SWITCH
AND 13A
SWITCHSOCKET OUTLET

K5061WHI

45A
DP MAIN SWITCH
AND 13A
SWITCHSOCKET OUTLET
WITH NEONS

1**K5040WHI**

45A
DP MAIN SWITCH
AND 13A
SWITCHSOCKET OUTLET

K5041WHI

45A
DP MAIN SWITCH
AND 13A
SWITCHSOCKET OUTLET
WITH NEONS

1**K5011WHI**

45A
DP MAIN SWITCH
AND 13A
SWITCHSOCKET OUTLET
WITH NEONS

1**K5001WHI**

45A
DP MAIN SWITCH
AND 13A
SWITCHSOCKET OUTLET
WITH NEONS

1

MOUNTING BOX

FLUSH:
877ZIC (46mm)

Supplied complete with terminal block, each terminal of which will accommodate up to two 10mm² conductors.

Moulded cover plate, cable clamp included.

DIMENSIONS:
86 x 86mm

FIXING CENTRES:
60.3mm

BS 5733: 2010

MOUNTING BOXES:

FLUSH:
886ZIC (Up to 6mm² conductor)
878ZIC (Up to 10mm² conductor)

Rotary operated shutter.

DIMENSIONS:
86 x 146mm

FIXING CENTRES:
120.6mm

BS 4177: 1992

Supplied complete with mounting box and cable restraint.

Fitted with earth terminals.

Rotary operated shutter.

DIMENSIONS:
86 x 146 x 60mm

BS 4177: 1992

MOUNTING BOX

FLUSH:
512OALM

Fitted with earth terminals.

Rotary operated shutter.

DIMENSIONS:
178 x 165mm

BS 4177: 1992

Supplied complete with mounting box.

Fitted with earth terminals.

Rotary operated shutter.

DIMENSIONS:
156 x 144 x 67mm

KNOCKOUTS:
5 x 25mm.
Two in each of top and bottom,
one in back.

BS 4177: 1992