

## Dual Switch

## DP Switches

20 AMP  
FLUSH



K5208WHI



K5207WHI

20 AMP  
FLUSH



K5403WHI



K5423WHI



K5423WHWHI



K5423D1WHI

32 AMP  
FLUSH



K5105WHI

50 AMP  
MOULDED  
FLUSH



K5205WHI



K5215CKWHI

50 AMP  
METAL



K5230WHI



K5012WHI

**K5208WHI**  
**K5207WHI**  
WITH NEON

10  
10

**K5403WHI**  
WITH FLEX OUTLET IN BASE

**K5423WHI**  
WITH FLEX OUTLET IN BASE  
AND NEON

**K5423WHWHI**  
WITH FLEX OUTLET IN BASE,  
NEON AND MARKED  
'WATER HEATER'.

**K5423D1WHI**  
WITH FLEX OUTLET IN BASE,  
NEON AND RED ROCKER

10  
10  
10  
10

**K5105WHI**  
WITH NEON  
**K5105GRA**  
WITH NEON

10  
10

**K5205WHI**  
**K5215WHI**  
WITH NEON  
**K5215CKWHI**  
WITH NEON  
AND MARKED 'COOKER'  
**K5215SHWHI**  
WITH NEON  
AND MARKED 'SHOWER'

1  
1  
1  
1

**K5230WHI**  
WITH NEON  
SURFACE MOUNTED

**K5012WHI**  
WITH NEON  
FLUSH MOUNTED

1  
1

FOR CONTROLLING DUAL  
IMMERSION HEATERS

MOUNTING BOXES:

FLUSH:  
866ZIC (35mm)

SURFACE:  
K2140WHI

Only mounting boxes with an earth  
terminal should be used.

These products are marked 'on' and  
'off' against the one-way DP switch  
and 'sink' and 'bath' against the  
two-way SP switch.

DIMENSIONS: 86 x 86mm  
FIXING CENTRES: 60.3mm

BS EN 60669-1: 1999

MOUNTING BOXES:

FLUSH:  
866ZIC (35mm)

SURFACE:  
K2140WHI  
K2031WHI (for extra wiring space)

Base entry frontplates are  
12.5mm deep.

All switches are complete with  
earth terminals.

Not recommended for switching  
large banks of PCs.

DIMENSIONS:  
86 x 86mm

FIXING CENTRES:  
60.3mm

BS EN 60669-1: 1999

MOUNTING BOXES:

FLUSH:  
866ZIC (6mm<sup>2</sup> conductors)  
877ZIC (10mm<sup>2</sup> conductors)

SURFACE:  
K2140WHI (6mm<sup>2</sup> conductors)  
K2031WHI (10mm<sup>2</sup> conductors)

Supplied with 8 self-adhesive  
plastic identification labels marked  
hob, fan, oven, water heater,  
shower, air conditioner, cooker and  
washing machine.

Not recommended for switching  
large banks of PCs.

DIMENSIONS: 86 x 86mm  
FIXING CENTRES: 60.3mm

BS EN 60669-1: 1999

MOUNTING BOXES:

FLUSH:  
886ZIC (6mm<sup>2</sup> conductors)  
878ZIC (10mm<sup>2</sup> conductors)

SURFACE:  
K2172WHI

**K5205WHI** and **K5215WHI**  
Supplied with 8 self-adhesive  
plastic identification labels marked  
hob, fan, oven, water heater,  
shower, air conditioner, cooker and  
washing machine.

Not recommended for switching  
large banks of PCs.

DIMENSIONS: 86 x 146mm  
FIXING CENTRES: 120.6mm

BS EN 60669-1: 1999

**K5230**

Supplied with mounting box. Earth  
terminal fitted on base of box.

Not recommended for switching  
large banks of PCs.

DIMENSIONS: 150 x 89 x 50mm  
KNOCKOUTS: 8 x 20mm

TERMINAL CAPACITY:  
16mm<sup>2</sup> conductors

BS EN 60669-1: 1999

**K5012**

Not supplied with mounting box.  
FLUSH: 5120ALM

Supplied with earth terminals.

Not recommended for switching  
large banks of PCs.

DIMENSIONS: 178 x 165mm

BS EN 60669-1: 1999