

Dual Switch

DP Switches

20 AMP
FLUSH



K5208WHI



K5207WHI

20 AMP
FLUSH



K5403WHI



K5423WHI



K5423WHWHI



K5423D1WHI

32 AMP
FLUSH



K5105WHI

50 AMP
MOULDED
FLUSH



K5205WHI



K5215CKWHI

50 AMP
METAL



K5230WHI



K5012WHI

K5208WHI
K5207WHI
WITH NEON

10
10

K5403WHI
WITH FLEX OUTLET IN BASE

K5423WHI
WITH FLEX OUTLET IN BASE
AND NEON

K5423WHWHI
WITH FLEX OUTLET IN BASE,
NEON AND MARKED
'WATER HEATER'.

K5423D1WHI
WITH FLEX OUTLET IN BASE,
NEON AND RED ROCKER

10
10
10
10

K5105WHI
WITH NEON
K5105GRA
WITH NEON

10
10

K5205WHI
K5215WHI
WITH NEON
K5215CKWHI
WITH NEON
AND MARKED 'COOKER'
K5215SHWHI
WITH NEON
AND MARKED 'SHOWER'

1
1
1
1

K5230WHI
WITH NEON
SURFACE MOUNTED

K5012WHI
WITH NEON
FLUSH MOUNTED

1
1

FOR CONTROLLING DUAL
IMMERSION HEATERS

MOUNTING BOXES:

FLUSH:
866ZIC (35mm)

SURFACE:
K2140WHI

Only mounting boxes with an earth
terminal should be used.

These products are marked 'on' and
'off' against the one-way DP switch
and 'sink' and 'bath' against the
two-way SP switch.

DIMENSIONS: 86 x 86mm
FIXING CENTRES: 60.3mm

BS EN 60669-1: 1999

MOUNTING BOXES:

FLUSH:
866ZIC (35mm)

SURFACE:
K2140WHI
K2031WHI (for extra wiring space)

Base entry frontplates are
12.5mm deep.

All switches are complete with
earth terminals.

Not recommended for switching
large banks of PCs.

DIMENSIONS:
86 x 86mm

FIXING CENTRES:
60.3mm

BS EN 60669-1: 1999

MOUNTING BOXES:

FLUSH:
866ZIC (6mm² conductors)
877ZIC (10mm² conductors)

SURFACE:
K2140WHI (6mm² conductors)
K2031WHI (10mm² conductors)

Supplied with 8 self-adhesive
plastic identification labels marked
hob, fan, oven, water heater,
shower, air conditioner, cooker and
washing machine.

Not recommended for switching
large banks of PCs.

DIMENSIONS: 86 x 86mm
FIXING CENTRES: 60.3mm

BS EN 60669-1: 1999

MOUNTING BOXES:

FLUSH:
886ZIC (6mm² conductors)
878ZIC (10mm² conductors)

SURFACE:
K2172WHI

K5205WHI and **K5215WHI**
Supplied with 8 self-adhesive
plastic identification labels marked
hob, fan, oven, water heater,
shower, air conditioner, cooker and
washing machine.

Not recommended for switching
large banks of PCs.

DIMENSIONS: 86 x 146mm
FIXING CENTRES: 120.6mm

BS EN 60669-1: 1999

K5230

Supplied with mounting box. Earth
terminal fitted on base of box.

Not recommended for switching
large banks of PCs.

DIMENSIONS: 150 x 89 x 50mm
KNOCKOUTS: 8 x 20mm

TERMINAL CAPACITY:
16mm² conductors

BS EN 60669-1: 1999

K5012

Not supplied with mounting box.
FLUSH: 5120ALM

Supplied with earth terminals.

Not recommended for switching
large banks of PCs.

DIMENSIONS: 178 x 165mm

BS EN 60669-1: 1999