

## Euro Multimedia Modules

TV CO-AXIAL OUTLETS  
FOR DIGITAL TV  
SCREENED  
NON ISOLATED

AUDIO &amp; HD



K5850WHI K5850BLK



K5851WHI K5851BLK



K5855WHI K5855BLK



K5852WHI



K5852DABWHI



K5853WHI



K5853DABWHI



K5854DABWHI



K5807WHI



K5805WHI









K5806WHI



K5809WHI



K5809BLK

**K5850WHI**   
**K5850BLK**   
 SINGLE OUTLET (IEC MALE)  
 ONE MODULE 25 X 50MM  
**K5851WHI**   
**K5851BLK**   
 SINGLE OUTLET (IEC FEMALE)  
 ONE MODULE 25 X 50MM  
**K5855WHI**   
**K5855BLK**   
 SINGLE F-TYPE SATELLITE SOCKET  
 ONE MODULE 25 X 50MM







Fully screened non isolated TV outlets containing a combination of single, TV/FM Diplexer and TV/FM/SAT Triplexer for use within digital TV systems and interactive TV services. Single outlets for connection to a single TV, FM or Satellite co-axial aerial lead.

MOUNTING BOXES:  
Min box depth 32mm

DIMENSIONS:  
1 Module 25 x 50mm  
2 Module 50 x 50mm





BS 3041: 1997  
IEC 169-2: 1965  
BS EN 50083 & BS 5733: 2010  
where applicable

These products are fully compatible with Labgear TV distribution systems and are approved for use in "Sky Homes" and "Homes On" specifications



**K5852WHI**   
**K5852BLK**   
 TWIN OUTLET  
 TV/FM DIPLEXER  
 TWO MODULE 50 X 50MM  
 (IRELAND ONLY)  
**K5852DABWHI**   
**K5852DABBLK**   
 TWIN OUTLET TV-FM/DAB DIPLEXER  
 TWO MODULE 50 X 50MM  
**K5853WHI**   
**K5853BLK**   
 TRIPLE OUTLET  
 TV/FM/SATELLITE TRIPLEXER  
 TWO MODULE 50 X 50MM  
 (IRELAND ONLY)







TV/FM diplexer units for connection to a single co-axial aerial lead with combined TV and FM signals.  
 TV/FM/SAT triplexer units for connection to a single co-axial aerial lead with combined TV, FM and Satellite signals

PERFORMANCE  
SINGLE OUTLETS  
TV/FM IEC MALE OR FEMALE  
DC-950MHz  
SAT F-TYPE  
DC-1.75GHz

**K5853DABWHI**   
**K5853DABBLK**   
 TRIPLE OUTLET TV-FM/DAB-SAT  
 TRIPLEXER TWO MODULE 50 X 50MM  
**K5854DABWHI**   
**K5854DABBLK**   
 QUAD OUTLET TV-FM/DAB-2XSAT  
 TWO MODULE 50 X 50MM

TV/FM/SAT PRODUCTS  
OUTLET TV  
DIPLEXER  
5-65MHz  
470-862MHz  
87.5-108MHz  
N/A  
FM/DAB  
SAT  
N/A  
TV/FM/DAB/SAT PRODUCTS FOR DIGITAL RADIO  
OUTLET TV  
DIPLEXER  
5-65MHz  
470-862MHz  
87.5-230MHz  
N/A  
FM/DAB  
SAT OR SAT1  
SAT2

**K5807WHI**   
**K5807BLK**   
 FEMALE HDMI OUTLET  
 K5807 Female HDMI Outlet is HDMI 1.1, 1.2 and 1.3 compatible, HDCP compliant.  
 Data Rate: Up to 2.25 Gbps  
 Scan: Up to 1080p/1920x1200  
 Input Connector:  
1 x HDMI Female (Type A)  
 Output Connector:  
1 x HDMI Female (Type A)  
 Supports high resolution input:  
PC: VGA, SVGA,  
SXVGA (1280x1024) and UXGA (1600x1200, 1920x1200)  
 HDTV: 480p, 720p, 1080i and 1080p  
 HDMI input cable should be no larger than 20m.  
 Weight of product: 16g  
 Dimensions: 50 x 50 x 20mm

**K5805WHI**   
**K5805BLK**   
 AUDIO BINDING POST SET  
 FOR SINGLE LOUD SPEAKER  
**K5806WHI**   
**K5806BLK**   
 RCA TO SCREW TERMINATION SET  
 1 RED AND 1 BLACK  
**K5809WHI**   
**K5809BLK**   
 TRIPLE RCA TO SCREW  
 TERMINATION SET  
 1 YELLOW, 1 WHITE, 1 RED  
 WEIGHT: 23g  
 DIMENSIONS:  
50 x 25 x 28mm

OUTLET TV  
FM  
SAT1  
OUTLET TV  
FM  
SAT1  
SAT2  
TRIPLEXER  
5-65MHz  
470-862MHz  
87.5-108MHz  
950-2300MHz  
TRIPLEXER  
5-65MHz  
470-862MHz  
87.5-230MHz  
950-2300MHz  
5-2300MHz