

PRODUCT-DETAILS

GAM0404

KFE STR CONNECTORS 20X20MM



KFE STR CONNECTORS 20X20MM Fitting for Covered Conduit, Straight with External Male Thread, Conduit Size 20mm,
Fitting for Covered Conduit, Straight with External Male Thread, Conduit Size 20mm,
Fitting for Covered Conduit, Straight with External Male Thread, Conduit Size 20mm,
M20 Thread, Very High Mechanical and UV Protection, IP54 Rating, Nickel Plated Brass
5011949203785
7412200090
.06 lb 27.211 g

Container Information		
Package Level 1 Units	25 piece	
Package Level 2 Units	300 piece	
Package Level 2 Width	13 in 330 mm	

Package Level 2 Height	7 in
	178 mm
Package Level 2 Depth /	13 in
Length	330 mm

Additional Information	
Application	For Insertion Into Threaded Entries and Knockouts Using a Locknut to
	Secure
Brand / Label	Kopex
Color	Metallic
Insulation Class	IP54
Material	Brass
Number of Batteries	0
Product Name	brass fitting for conduit
Product Type	Metallic Fitting for Covered Conduit
Size	Conduit Size 20mm ; M20 Thread
Special Functions	Very High Mechanical and UV Protection
Standards	BSI Kitemark KM-90009, Low Voltage Directive
Surface Finishing	Nickel Plated
Temperature Range	Static: -50 to 350 °C Dynamic: -45 to 250 °C
UPC	786210277059

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	GAM0404
Declaration of Conformity - CE	9AKK107492A9617
Instructions and Manuals	GAM0404

Classifications		
ETIM 6	EC001180 - Screw connection for protective metallic hose	
ETIM 7	EC001180 - Screw connection for protective metallic hose	
UNSPSC	39121311	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	4441 >> Electrical fittings	

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Cable\ Protection,\ Explosion\ Proof\ and\ Lighting \rightarrow Flexible\ Cable\ Protection\ Systems$

GAM0404 3

