

25 piece

225 piece

13 in 330 mm

PRODUCT-DETAILS

Package Level 1 Units

Package Level 2 Units

Package Level 2 Width

GFM0404

KFE STRAIGHT CONNECTORS 20X20MM



7TCA297050R0059
501194920402
KFE STRAIGHT CONNECTORS 20X20MM
Fitting for Uncovered Conduit, Straight with External Male Thread, Conduit Size 20mm M20 Thread, Very High Mechanical and UV Protection, IP40 Rating, Nickel Plated Brass
5011949204027
7412200090
.06 lt 27.211 c

Package Level 2 Height	7 in
	178 mm
Package Level 2 Depth /	13 in
Length	330 mm

Additional Information	
Application	For Insertion Into Threaded Entries and Knockouts Using a Locknut to
	Secure
Brand / Label	Kopex
Color	Metallic
Insulation Class	IP40
Material	Brass
Number of Batteries	0
Product Name	brass fitting for conduit
Product Type	Metallic Fitting for Uncovered Conduit
Size	Conduit Size 20mm ; M20 Thread
Special Functions	Very High Mechanical and UV Protection
Standards	BSI Kitemark KM-90009, Low Voltage Directive
Surface Finishing	Nickel Plated
Temperature Range	Static: -50 to 350 °C Dynamic: -45 to 250 °C
UPC	786210277127

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	GFM0404
Declaration of Conformity - CE	9AKK107492A9617
Instructions and Manuals	GFM0404

Classifications	
ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121311
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4441 >> Electrical fittings

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Cable\ Protection,\ Explosion\ Proof\ and\ Lighting \rightarrow Flexible\ Cable\ Protection\ Systems$

GFM0404 3

