

PRODUCT-DETAILS

GFM0505

KFE STRAIGHT CONNECTORS 25X25MM



General Information

Extended Product Type	GFM0505
Product ID	7TCA297050R0061
EAN	5011949204034
Catalog Description	KFE STRAIGHT CONNECTORS 25X25MM
Long Description	Fitting for Uncovered Conduit, Straight with External Male Thread, Conduit Size 25mm, M25 Thread, Very High Mechanical and UV Protection, IP40 Rating, Nickel Plated Brass

Ordering

EAN	5011949204034
Customs Tariff Number	7907002000

Dimensions

Product Net Weight	.1 lb 45.351 g
--------------------	-------------------

Container Information

Package Level 1 Units	10 piece
Package Level 2 Units	200 piece
Package Level 2 Width	13 in 330 mm

Package Level 2 Height	7 in 178 mm
Package Level 2 Depth / Length	13 in 330 mm

Additional Information

Application	For Insertion Into Threaded Entries and Knockouts Using a Locknut to Secure
Brand / Label	Kopex
Color	Metallic
Insulation Class	IP40
Material	Brass
Number of Batteries	0
Product Name	zinc fitting for conduit
Product Type	Metallic Fitting for Uncovered Conduit
Size	Conduit Size 25mm ; M25 Thread
Special Functions	Very High Mechanical and UV Protection
Standards	BSI Kitemark KM-90009, Low Voltage Directive
Surface Finishing	Nickel Plated
Temperature Range	Static: -50 to 350 °C Dynamic: -45 to 250 °C
UPC	786210242699

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	GFM0505
Declaration of Conformity - CE	9AKK107492A9617
Instructions and Manuals	GFM0505

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121311
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4441 >> Electrical fittings

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

