

General Information

Extended Product Type:	KSE340TPN
Product ID:	2CMA142415R1000
EAN:	7392696424158
Catalog Description:	ENCL. SW#KSE 340 R TPN
Long Description:	Aluminum enclosed side operated switch-disconnectors, 3-pole, IP65. Enclosure in Aluminum alloy (Silumin) with metric threaded cable entries and handle in PBT plastic. Light grey box with dark grey cover and operating handle. Delivery includes PE+neutral terminal and membrane glands (IP54) / sealing plugs. For IP65 degree of protection compression glands must be used.

Categories

Products » Low Voltage Products and Systems » Enclosed Switches » Enclosed Switch-Disconnectors

Ordering

EAN:	7392696424158
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365015

Dimensions

Product Net Width:	138 mm
Product Net Height:	168 mm
Product Net Length:	68 mm
Product Net Depth:	168 mm
Product Net Weight:	0.80 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	139 mm
Package Level 1 Height:	169 mm
Package Level 1 Length:	70 mm
Package Level 1 Gross Weight:	0.80 kg
Package Level 1 EAN:	7392696424158

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2008 Q1
--------------	---

Additional Information

Cable Entry Position:	Top and bottom
Cable Outlets Per Side:	2xM25/2xM25+1xM16
Cable Throughouts:	32
Color:	Dark gray
Connecting Capacity Main Circuit:	10 mm ²
Conventional Free-air Thermal Current (I _{th}):	40 A
Degree of Protection:	IP54
Enclosure Material:	Aluminium
Handle Type:	Side-operated
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	3
Product Main Type:	KSE
Product Name:	Enclosed Switch-Disconnecter
Protection Type:	Splashproof
Rated Current (I _n):	40 A
Rated Insulation Voltage (U _i):	690 V
Rated Operational Current AC-22A (I _e):	(400 V) 40 A (500 V) 40 A (690 V) 25 A
Rated Operational Current AC-23A (I _e):	(400 V) 25 A (500 V) 25 A (690 V) 16 A
Rated Operational Power AC-23A (P _e):	(400 V) 11 kW (500 V) 15 kW

(690 V) 11 kW

RoHS Date:	2009-01
Standards:	IEC 60947-1,-3
Suitable For:	KSE
Suitable for Product Class:	Enclosed Switches

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC340009C0201
Declaration of Conformity - CE:	2CMC300009
RoHS Information:	2CMC300025D0001

Classifications

ETIM 4:	EC000216 - Switch disconnecter
ETIM 5:	EC000249 - Protection switch disconnecter housing
Object Classification Code:	2CMT005069
UNSPSC:	39120000

