

General Information

Extended Product Type:	KSE380TPN
Product ID:	2CMA144583R1000
EAN:	7392696445832
Catalog Description:	Encl. sw#KSE 380 TPN
Long Description:	Aluminum enclosed front operated switch-disconnectors, 3-pole, IP65. Enclosure in Aluminum alloy (Silumin) with metric threaded cable entries. Light grey box with dark grey cover. Operating handle in black BPT plastic. Delivery includes PE+neutral terminal and membrane glands (IP54) / sealing plugs. For IP65 degree of protection compression glands must be used.

Categories

Products » Low Voltage Products and Systems » Enclosed Switches » Enclosed Switch-Disconnectors

Ordering

EAN:	7392696445832
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365015

Dimensions

Product Net Width:	160 mm
Product Net Height:	150 mm
Product Net Length:	230 mm
Product Net Depth:	150 mm
Product Net Weight:	1.75 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	170 mm
Package Level 1 Height:	240 mm
Package Level 1 Length:	150 mm
Package Level 1 Gross Weight:	1.75 kg
Package Level 1 EAN:	7392696445832

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-06-01
--------------	--

Additional Information

Cable Entry Position:	Top and bottom
Cable Outlets Per Side:	2xM40/2xM40+1xM16
Cable Throughouts:	40
Conventional Free-air Thermal Current (I_{th}):	80 A
Degree of Protection:	IP65
Enclosure Material:	Aluminium
Handle Type:	Front-operated
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	3
Product Main Type:	KSE
Product Name:	Enclosed Switch-Disconnecter
Protection Type:	Watertight
Rated Current (I_n):	80 A
Rated Insulation Voltage (U_j):	750 V
Rated Operational Current AC-22A (I_e):	(500 V) 80 A (690 V) 80 A
Rated Operational Current AC-23A (I_e):	(400 V) 75 A
Rated Operational Power AC-23A (P_e):	(400 V) 37 kW (500 V) 37 kW (690 V) 18.5 kW
RoHS Date:	2009-01
Standards:	IEC 60 947-3

Suitable For:	KSE
Suitable for Product Class:	Enclosed Switches

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC340009C0201
RoHS Information:	2CMC300009

Classifications

E-nummer:	44583
ETIM 4:	EC000216 - Switch disconnecter
ETIM 5:	EC000249 - Protection switch disconnecter housing
Object Classification Code:	2CMT005069
UNSPSC:	39120000

