

5 piece

1 in 25 mm

1 in

PRODUCT-DETAILS

Package Level 2 Units

Package Level 2 Width

Package Level 2 Height

GFM0606

KFE STR UNCOVRD COND CONN 32X32MM



General Information Extended Product Type	GFM0606
Product ID	7TCA297050R0062
EAN	5011949204041
Catalog Description	KFE STR UNCOVRD COND CONN 32X32MM
Long Description	Fitting for Uncovered Conduit, Straight with External Male Thread, Conduit Size 32mm M32 Thread, Very High Mechanical and UV Protection, IP40 Rating, Nickel Plated Brass
Ordering	501104020404
EAN	5011949204043
Customs Tariff Number	7907001000
Dimensions	
Product Net Weight	.16 lb
	72.562 g
Container Information	

	25 mm
Package Level 2 Depth /	1 in
Length	25 mm

Additional Information	
Application	For Insertion Into Threaded Entries and Knockouts Using a Locknut to
	Secure
Brand / Label	Корех
Color	Metallic
Insulation Class	IP40
Material	Brass
Number of Batteries	0
Product Name	ZINC FITTING FOR TUBES AND PIPES
Product Type	Metallic Fitting for Uncovered Conduit
Size	Conduit Size 32mm ; M32 Thread
Special Functions	Very High Mechanical and UV Protection
Standards	BSI Kitemark KM-90009, Low Voltage Directive
Surface Finishing	Nickel Plated
Temperature Range	Static: -50 to 350 °C
	Dynamic: -45 to 250 °C
UPC	786210242705

Certificates and Declarations (Document Number) Data Sheet, Technical GFM0606 Information Declaration of 9AKK107492A9617 Conformity - CE Instructions and GFM0606 Manuals

Classifications		
ETIM 6	EC001180 - Screw connection for protective metallic hose	
ETIM 7	EC001180 - Screw connection for protective metallic hose	
UNSPSC	39121311	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	4441 >> Electrical fittings	

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Lost and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Cable\ Protection,\ Explosion\ Proof\ and\ Lighting\ \rightarrow\ Flexible\ Cable\ Protection\ Systems$

GFM0606 3

