

PRODUCT-DETAILS

KEBF0530

KE LOW ACID PVC CONDUIT 25MM 30M



General Information

Extended Product Type	KEBF0530
Product ID	7TCA297050R0134
EAN	5011949220782
Catalog Description	KE LOW ACID PVC CONDUIT 25MM 30M
Long Description	Liquid Resistant, Highly Flexible Conduit, Nominal Conduit Size 25mm, 3/4 Inch US Trade Size, Outside Diameter 25.7mm, Inside Diameter 21.1mm, Static Bend Radius 50mm, Reel Length 30 Meters, IP54, IP65 Rating, Galvanised Steel Core with PVC Jacket, Black

Ordering

EAN	5011949220782
Customs Tariff Number	3926909990

Dimensions

Product Net Weight	22.05 lb 10 kg
--------------------	-------------------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Kopex
Color	Black
Flexibility	High
Inside Diameter	21.1 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	3/4 in
Number of Batteries	0
Outside Diameter	25.7 mm
Product Name	pvc conduit
Product Type	Liquid Resistant Conduit
Radius	Static: 50 mm
Standards	BSI Kitemark KM-90009, Low Voltage Directive
UPC	786210246260

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	KEBF0530
Declaration of Conformity - CE	9AKK107492A9617
Instructions and Manuals	KEBF0530

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

