

## RAMCRO BMS - Audio, Control & Instrumentation Cable MULTI CONDUCTOR CABLE

LSZH(FRNC) sheathed, screened cable with 18 AWG conductors

Code: SAS0405HXEDX-RB

### Application

LSZH - FRNC sheathed multi-conductor cables are suitable for Building Management Systems (BMS), Sound, Audio, Security, Safety, Control and Instrumentation.


### Construction

		Unit	Nominal Value
Formation	4 Cores		
Section	18 AWG		
Conductor	Plain annealed copper wire, 7 strand	mm	1,1
Insulation	Polyolephine	mm	1,5
Colour Code	Black, Red, White, Green		
Individual Screen	N.A.		
Wrapping	at least 1 layer of plastic tape 0,023 mm		
Collective Screen	0,026 mm Aluminium / PETP tape over tinned copper drain wire		
Inner Sheath	N.A.		
Armour	N.A.		
Outer Sheath	Thermoplastic Low Smoke, Halogen Free - LSZH (FRNC) - Purple RAL 4005	mm	4,6
Cable Printing	RAMCRO MADE IN ITALY R1725 AUDIO CONTROL & INSTRUMENTATION CABLE 4C 18AWG SCREENED LSZH (FRNC) 300 V 75 C IEC 60332-1/UL 1581 -SAS0405HXEDX-RB- "PROD.WEEK/18" + BATCH + METER MARKING		

### Technical Data & Standard References

Fire Propagation:		Type of Cable:	Audio, Control & Instrumentation Cable
- Test on single cable	IEC 60332-1	Low Voltage Directive	2014/35/UE
- Test on bunched cables	IEC 60332-3	Other References:	
Smoke Density	IEC 61034		
Amount of Halogen acc. to IEC 60754-1 & EN50267-1	ZERO		
Acidity (ph value) and conductivity	IEC 60754-2		
Sunlight resistance	UL 1581 section 1200		
Notes			

### Electrical & Mechanical Data

Conductor Cross-section	Nom.	18 AWG	Temperature Range:		
DC Resistance per core at 20° C	max	Ω/km	22,7	During Operation	° C -30°C up to 80°C
Insulation Resistance at 20° C	min	MΩ*km	25	During Installation	° C -30°C up to 80°C
Nominal Mutual Capacitance	max	pF/m	150		
Inductance	max	mH/km	1	Min. Bending Radius	mm 8 x cable diameter
Test Voltage - Core/Core	V	2000		Max Pulling Tension	N/mm2 156
Test Voltage - Core/Screen	V	2000		Weight Approx	kg/km 49
Operating Voltage	V	300		Put up length	mt 305

Issued by: RAMCRO S.p.A.



Date of issue:

Prepared by RAMCRO Tech

Via Marzorati, 15 - 20014 Nerviano - Milan - Italy / www.ramcro.it

18/09/2018 00:00

Creator: LDG

Transfer to third parties only under authorization by Ramcro S.p.A.

Empty Form

Printing errors excepted. Subject to alterations.