MANUFACTURER: SRW Products

ADDRESS: 32020 126<sup>th</sup> Street

Princeton, MN 55371

EMERGENCY PHONE: 1-800-424-9300 INFORMATION PHONE: 1-800-752-9326 NAME OF PREPARER: Safety Director

Date Printed: 01-01-2021

PRODUCT NAME: Dual Wash

PRODUCT CODE: SSDW

HAZARD RISK CLASSIFICATION

SIGNAL WORD: DANGER

PICTOGRAM:

GHS05 - CORROSION GHS07 - EXCLAMATION MARK

HAZARD CLASS HAZARD CATEGORY

CORROSIVE TO METALS CATEGORY 1

SKIN CORROSION CATEGORY 1 IRRITATION TOXIC TO SPECIFIC TARGET ORGAN CATEGORY 3 TOXICITY -

SINGLE EXPOSURE

HAZARD STATEMENTS:

H290 May be corrosive to metal. H303 May be harmful if swallowed

H314 Causes severe skin burns and eye damage

H335 May cause respiratory irritation

PRECAUTIONARY STATEMENTS: PREVENTION:

P234 Keep only in original packaging.

P260 Do not breath dusts/fume/gas/mist/vapors or spray.

P264 Wash hands and any exposed area thoroughly after handling. P271

Use only outdoors or in well-ventilated area.

P280 Wear protective impervious gloves/ OSHA approved eye protection/face

protection.

RESPONSE:

P301+P312 If swallowed: Call a Poison Center / doctor if you feel unwell.

 ${\tt P301+P330+P331\ If\ swallowed:\ Rinse\ mouth.\ Do\ NOT\ induce\ vomiting.}$ 

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower).

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/ emergency responder. P312

Call a POISON CENTER/doctor if you feel unwell.

P321 Specific treatment (see on this label)

P330 Rinse mouth.

P363 Wash contaminated clothing before reuse. P390

Absorb spillage to prevent material damage.

STORAGE:

P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405

Store locked up.

P406 Store in corrosive resistant/ . . . container with a resistant

inner liner.

DISPOSAL:

P501 Store separately. Dispose of contents/ container in accordance

with local/ regional/national /international regulations.

# ====== SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS ==

WEIGHT EXPOSURE LIMITS

2 MG/M3

CAS NUMBER PERCENT OSHA PEL ACGIH TLV OTHER

Sodium Metasilicate Pentahvd 6834-92-0 10-25

#### PRIMARY ROUTES OF EXPOSURE:

Skin contact.

COMPONENT

### EFFECTS OF ACUTE EXPOSURE:

EYES: Corrosive to eyes. Contact with eyes may cause severe irritation and burns.

SKIN: Corrosive to skin and mucous membranes. Contact with skin may cause severe irritation and burns. May be absorbed through skin in toxic amounts.

INHALATION: Inhalation of vapor or mist can cause irritation of nose, throat and lungs and lead to headaches and nausea.

INGESTION: Not an anticipated route of exposure. Small amounts are not expected to be harmful. CHRONIC HEALTH EFFECTS:

No anticipated chronic effects. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

No known effects on other illnesses.

EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek medical attention.

SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing. INGESTION:

If a large amount is ingested, give water or milk and induce vomiting. Seek medical attention.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

METHOD USED: n/a

## ====== SECTION 5 - FIRE AND EXPLOSION HAZARD DATA ==============

FLASH POINT: No flash

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: n/a

UPPER: n/a

#### EXTINGUISHING MEDIA:

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide.

### SPECIAL FIREFIGHTING PROCEDURES:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out.

### UNUSUAL FIRE AND EXPLOSION HAZARDS:

There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

## == SECTION 6 - ACCIDENTAL RELEASE MEASURES ====== STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Do not let uncured spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water. Wear appropriate protective equipment.

#### HANDLING INFORMATION:

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communication Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

### STORAGE INFORMATION:

Keep from freezing; material may coagulate. The minimum recommended storage temperature is 34F/1C, the maximum recommended storage temperature is 120F/49C. Keep away from incompatible materials (see section 10). Keep containers tightly closed. It is advised that material be used within 1 year of manufacture, rotate stock.

# OTHER PRECAUTIONS:

All empty containers should be disposed of in an environmentally safe manner in accordance with all governmental regulations.

# ====== SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION ========

#### RESPIRATORY PROTECTION:

No special requirements under normal use conditions. In confined areas, or areas with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant.

#### VENTILATION

General room ventilation is adequate.

#### PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing chemical resistant gloves and other appropriate protective clothing. Launder contaminated clothing before reuse.

#### EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

#### OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.

#### WORK/HYGIENIC PRACTICES:

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidelines.

## ========== SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES ===========

PHYSICAL STATE: Liquid COLOR: Various colors

ODOR: Amine or ammonia odor SOLUBILITY IN WATER: Dilutable

SPECIFIC GRAVITY (H2O=1): 1.12 VAPOR DENSITY: Heavier than air.

BOILING RANGE: EVAPORATION RATE: Slower than nBuAc

COATING V.O.C.: 0 g/l (0.0 lb./gal)

### 

Stable under normal conditions and handling.

#### CONDITIONS TO AVOID:

None known

## INCOMPATIBILITY (MATERIALS TO AVOID):

None known. Materials which are not compatible with water or ordinary organics will not be compatible with this material.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Combustion may liberate toxic byproducts such as carbon dioxide, and carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.

### HAZARDOUS POLYMERIZATION:

Will not occur.

# 

### SENSITIZATION:

None known.

### CARCINOGENICITY:

There is no data available to indicate any components present at greater than 0.1% may present a carcinogenic hazard.

# REPRODUCTIVE TOXICITY:

There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity. There is no data available to indicate any components present at greater than 0.1% may cause birth defects.

## MUTAGENICITY:

There is no data to indicate that any component present at greater than 0.1% will alter DNA.

# 

Contains ammonia or amines which may be toxic to aquatic life.

# 

This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261, however, state and local regulations may be more restrictive. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.

SHIPPING NAME:

UN1719, Caustic Alkali Liquids, N.O.S., (Disodium Trioxosilicate, Pentahydrate), 8, III

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Substances Control Act (TSCA) chemical substance inventory. This product does not contain a chemical subject to the reporting requirements of SARA Title III, Section 313 (40CFR

372) above de minimis concentrations.

## STATE SPECIFIC REQUIREMENTS:

STATE LISTED COMPONENTS

This product does not contain a chemical known to the state of California to cause cancer, birth defects or reproductive harm, subject to the requirements of California Proposition 65.

STATE CODE

REVISION DATE: 11/16/88

HMIS CODES: H F R Ρ В

CAS NUMBER

1 0 0