



TECHNICAL DATA SHEET

HG Paver Seal™

Water-Based High-Gloss Sealer



NOTICE

Make sure you have an up-to-date technical data sheet by referencing our website: SRWProducts.com

DESCRIPTION

High Gloss sealer provides a high-gloss, wet-look protective barrier that prolongs the life of any paver project. Use this product to protect and beautify a paver's appearance.

APPLICATIONS

- Concrete Pavers

PROPERTIES

- High-gloss, wet-look finish
- Minimizes salt and freeze/thaw damage
- Provides UV protection
- Stabilizes joint sand from washout, weeds & ants
- Color enhancing

COVERAGE

COVERAGE	
Size	Sq. Ft.
1 gal	150 Sq. Ft.
5 gal	750 Sq. Ft.

USER TIPS

- Test in an inconspicuous area before starting the general application to ensure desired results and expected finish.
- Always follow paver manufacturer's sealing recommendations.
- If using on manufactured stone, ask dealer about cleaning and sealing procedures prior to application. Care should be taken for vertical surface application where runs may alter the finish.
- For a deeper sheen, wait at least 4 hours before applying a second coat. This ensures the highest gloss appearance. Do not over apply.
- For added slip resistance, use SRW SR Slip-Resist™.
- Do not use more than one sealer on the same project.

SRW Products
800-752-9326

32005 126th St.
PO Box 70
Princeton, MN 55371

SRWProducts.com

Revised: 03-22-2021

HG Paver Seal™ Technical Data Sheet

Page 1 of 3

INSTALLATION INSTRUCTIONS

CLEAN

1. Wait 28 days after installing polymeric sand before sealing.
2. Thoroughly sweep surface of joint sand or loose material.
3. Spot clean if needed with one of the SRW Specialty Clean™ products. Then, prepare all pavers with a SRW Products General Purpose Cleaner.

CLIMATE

4. After cleaning, wait at least 24 hours before sealing. Surface and joints must be completely dry.
5. Recommended application temperatures are 50°F - 80°F (10°C - 27°C) from installation through the cure process.
6. Do not apply if inclement weather is forecasted within 24 hours.

APPLY

7. STIR THOROUGHLY.
8. Apply with an SRW Products approved Slit Foam Roller and sprayer.
9. For best results, spray then back roll. This prevents an uneven finish. A 2-person application is recommended.
10. Start at the highest project elevation. Do not allow sealer to pool on pavers or in joints.
11. Repeat if desired.

CURE

12. Allow sealed area to dry and cure 24 hours.
13. Protect area from water and rain until dry.

Dry-tack free: 25 minutes

Foot traffic: 24 hours

Vehicle traffic: 72 hours

Note: All calculations based on 68°F – 77°F (20°C – 25°C)

STORAGE AND SHELF LIFE

Keep from freezing. Store container in a cool area with cap or lid firmly in place.

CLEAN UP

Rinse off all equipment with soap and water and let dry.

WARNINGS

CAUTION: Protect buildings, landscaping and vehicles from overspray or spray drift.

WARNING: Do not inhale spray mist. Irritating to skin and eyes. Always wear a mask and protective eyewear and clothing. See SDS for further information.

IMPORTANT NOTICE: Contains Water (7732-18-5), Solvent Naphtha (petroleum) Light Aromatic (64742-95-6), Acrylic Copolymer (28262-63-7), Plasticizer (6422-86-2), Ester Alcohol (25265-77-4). Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only. For professional use only. Test in a small, discrete area before use.

FIRST AID: EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek medical attention. SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing. INGESTION: **DO NOT INDUCE VOMITING.**

Immediately administer 1-2 glasses of water and seek medical attention. INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

HMIS RATING: *Hazard Index 2=moderate hazard, 0=minimal hazard*

Health 2, Flammability 2, Reactivity 0, Protection I

SHIPPING

DOT Shipping Name: Not Regulated.

PACKAGING

Paver Seal™ HG High Gloss			
PART #	SIZE	AMT PER CTN	QUANTITY
SSPSRO CTN	1 gal	4/CTN	36 CTNS/PLT
SSPSRO 5GAL	5 gal	1	36/PLT

SRW Products

800-752-9326

32005 126th St.

PO Box 70

Princeton, MN 55371

SRWProducts.com

Revised: 03-22-2021

HG Paver Seal™ Technical Data Sheet

Page 3 of 3