Revision Date: 01-01-2024 MANUFACTURER: SRW Products 32020 126<sup>th</sup> Street ADDRESS: Princeton, MN 55371 RECOMMENDED USE: PAINT OR PAINT RELATED MATERIAL PRODUCT NAME: SRW JS- Joint Stabilizing Sealer PRODUCT CODE: 800-752-9326 24 HOUR EMERGENCY PHONE: CHEMTREC 1-800-424-9300 HAZARD RISK CLASSIFICATION SIGNAL WORD: WARNING PICTOGRAM: GHS07 - EXCLAMATION MARK

# HAZARD CLASS HAZARD CATEGORY

ACUTE TOXICITYCATEGORY 4ORALACUTE TOXICITYCATEGORY 4DERMALACUTE TOXICITYCATEGORY 4INHALATIONSKIN CORROSION /IRRITATIONCATEGORY 2SERIOUS EYE DAMAGE /CATEGORY 2SERIOUS EYE DAMAGE /CATEGORY 2AND 2AEYE IRRITATIONCATEGORY 2CATEGORY 2

#### HAZARD STATEMENTS:

H302+H312+H332Harmful if swallowed, in contact with skin or if inhaledH315Causes skin irritationH319Causes serious eye irritation.

# PRECAUTIONARY STATEMENTS:

# **PREVENTION:**

P210	Keep away from heat/hot surfaces/sparks/open flames and other
	sources of ignition. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapor/ spray.
P264	Wash hands and any exposed area thoroughly after handling.
P270	Do not eat, drink or smoke while using this product.
P271	Use only outdoors or in well-ventilated area.
P280	Wear protective impervious gloves/ OSHA approved eye
	protection/face protection.

#### **RESPONSE:**

P301+P310	If swallowed: Immediately call a Poison Center/doctor.
P302+P350	If on skin: Wash with plenty of soap and water.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable
	for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several
	minutes. Remove contact lenses, if present and easy to do.
	Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P321	Specific treatment (see on this label)
P330	Rinse mouth.
P332+P313	If skin irritation occurs: Get medical advice/attention.

P337+P313	If eye irritation persists: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P370+P378	in case of fire: Use carbon dioxide (CO2), powder, alcohol resistant, foam to extinguish.
	100100ano, 10am 00 0n01nga10n.

#### STORAGE :

P405 Store locked up.

#### DISPOSAL:

P501 Store separately. Dispose of contents/ container in accordance with local/ regional/national /international regulations.

# OTHER HAZARDS: NONE KNOWN

**HMIS RATING: H F R PPE** 2 0 0 B

COMPONENT	CAS NUMBER	WEIGHT PERCENT		URE LIMITS ACGIH TLV	OTHER
+ 2-Butoxyethanol	111-76-2	1.2	25 PPM	25 PPM	

+Toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

Skin contact.

# DESCRIPTION OF FIRST AID MEASURES:

EYES:	Flush with large amounts of water for 15 minutes, lifting
	upper and lower eyelids. If irritation persists, seek
	medical attention.
SKIN CONTACT:	Wash contaminated area with soap and water. Remove and
	launder contaminated clothing.
INGESTION:	If a large amount is ingested, give water or milk and
	induce vomiting. Seek medical attention.
INHALATION:	Remove victim to fresh air and provide oxygen if breathing
	is difficult. If breathing has stopped administer
	artificial respiration. Seek medical attention if condition
	persists.

# MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

SIMPIONS/EFFECIS, ACOLE AND DELAIED:		
Direct contact with eyes may cause irritation.		
Prolonged or repeated contact may cause irritation.		
2-Butoxyethanol may be absorbed through skin and		
produce toxic effects similar to those resulting from		
inhalation exposure.		
Inhalation of vapor or mist can cause irritation of nose,		
throat and lungs and lead to headaches and nausea.		

**INGESTION:** Not an anticipated route of exposure. Small amounts are not expected to be harmful.

#### CHRONIC HEALTH EFFECTS:

No anticipated chronic effects.

# MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

No known effects on other illnesses.

**INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:** Treat symptomatically.

# SUITABLE EXTINGUISHING MEDIA:

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide.

# SPECIFIC HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

In the event of fire, harmful vapors including carbon monoxide, carbon dioxide, and others may be released. There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

#### SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area and keep unauthorized personnel out.

# 

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:** Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use proper personal protective equipment listed in section 8.

**ENVIRONMENTAL PRECAUTIONS:** Keep runoff from storm sewers, ditches, streams, lakes and other ground waters and waterways.

#### METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP:

Contain all spills. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Collect into suitable containers and dispose of properly in accordance with all applicable regulations. (See Section 13) Rinse affected area thoroughly with water.

#### 

# PRECAUTIONS FOR SAFE HANDLING:

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communication Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

#### PRECAUTIONS FOR SAFE STORAGE:

Keep from freezing; material may coagulate. The minimum recommended storage temperature is 34F/1C, the maximum recommended storage temperature is 120F/49C. Keep away from incompatible materials (see section 10). Keep containers tightly closed. It is advised that material be used within 1 year of manufacture, rotate stock.

# OTHER PRECAUTIONS:

All empty containers should be disposed of in an environmentally safe manner in accordance with all governmental regulations.

# 

CONTROL PARAMETERS: SEE SECTION 3 FOR OCCUPATIONAL EXPOSURE LIMIT VALUES ENGINEERING CONTROLS: General room ventilation is adequate.

# PERSONAL PROTECTVE EQUIPMENT:

# RESPIRATORY PROTECTION:

No special requirements under normal use conditions. In confined areas, or areas with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant.

#### PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing chemical resistant gloves and other appropriate protective clothing. Launder contaminated clothing before reuse.

# EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI 287.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

#### OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.

#### WORK/HYGIENIC PRACTICES:

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up

# 

APPEARANCE/PHYSICAL STATE: Liquid	COLOR: Various colors
ODOR: Amine or ammonia odor	pH: Not Determined
ODOR THRESHOLD: Not measured	SOLUBILITY IN WATER: Dilutable
MELTING/FREEZING POINT: Not Determined	BOILING POINT/RANGE:
SPECIFIC GRAVITY (H2O=1): 1.	VAPOR DENSITY: Greater Than Air
EVAPORATION RATE: Not Determined	FLAMMABILITY: Not determined
FLASH POINT: No flash TCC	VAPOR PRESSURE: Not Determined
UPPER EXPLOSION LIMIT: n/a	AUTO-IGNITION TEMPERATURE: Not Determined
LOWER EXPLOSION LIMIT: n/a	PARTITION COEFFICIENT: Not Available
DECOPMPOSITION TEMPERATURE: n/a	VISCOSITY: Not Determined
COATING V.O.C.: 112 g/l (0.94 lb./gal)	

#### 

**REACTIVITY:** Will not occur.

#### CHEMICAL STABILITY:

Stable under normal conditions and handling.

#### POSSIBILITY OF HAZARDOUS REACTIONS:

No hazardous reactions if stored and handled as prescribed/indicated.

#### CONDITIONS TO AVOID:

None known

# INCOMPATIBLE MATERIALS:

None known. Materials which are not compatible with water or ordinary organics will not be compatible with this material.

# HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Combustion may liberate toxic byproducts such as carbon dioxide, and carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.

#### 

#### SENSITIZATION:

None known.

# CARCINOGENICITY:

There is no data available to indicate any components present at greater than 0.1% may present a carcinogenic hazard.

# REPRODUCTIVE TOXICITY:

2-Ethoxyethanol has been suggested as a cause of male and female reproductive fertility effects, and testis damage.

# TERATOGENICITY (BIRTH DEFECTS):

Yes.

# **MUTAGENICITY:** 2-Butoxyethanol may cause blood disorders based on animal data.

ECOTOXICITY: No data available.

#### PERSISTENCE AND DEGRADABILITY:

Not readily degradable.

# BIOACCUMULATIVE POTENTIAL:

No data available.

# MOBILITY IN SOIL:

No data available.

**OTHER ADVERSE EFFECTS:** No known effects or critical hazards. No data available.

#### 

This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261, however, state and local regulations may be more restrictive. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.

# 

**PROPER SHIPPING NAME: (UN #, SHIPPING NAME, HAZARD CLASS, PACKING GROUP)** Not regulated.

# 

# US TOXIC SUBSTANCE CONTROL ACT (TSCA):

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Substances Control Act (TSCA)chemical substance inventory.

SARA 302 EXTREMELY HAZARDOUS SUBSTANCE: None

SARA 311/312 HAZARDOUS CHEMICAL: See Section 3

#### SARA 313 (TRI REPORTING):

This product does contain a chemical(s) subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372). See section 3.

STATE LISTED COMPONENTS	CAS NUMBER	STATE CODE
2-Butoxyethanol	111-76-2	MA, NJ, PA

# CALIFORNIA PROPOSITION 65

This product contains a chemical(s) known to the state of California to cause cancer, birth defects or reproductive harm, which are subject to the requirements of California Proposition 65.

#### 

This version replaces all previous versions. The information contained in this SDS and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Although certain hazards are described herein, SRW Products, Inc. cannot guarantee that these are the only hazards that exist. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall SRW Products, Inc., assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. SRW Products, Inc., expressly disclaims any representations and warranties of any kind, whether express or implied, as to the accuracy, completeness, non-infringement, merchantability and/or fitness for a particular purpose with respect to any information and recommendations provided. SRW Products, Inc., reserves the right to make any changes to the information and/or recommendations at any time, without prior subsequent notice.