



TECHNICAL DATA SHEET

PS Paver Seal™

Water-Based Penetrating Sealer



NOTICE

Make sure you have an up-to-date technical data sheet by referencing our website: SRWProducts.com

DESCRIPTION

PS Penetrating Sealer offers the best paver protection from water intrusion, acid rain, deicing chemicals and freeze/thaw exposure. It is easy to apply and retains the original appearance of pavers.

APPLICATIONS

- Concrete Pavers
- Clay Pavers
- Concrete Permeable Pavers
- Retaining Walls
- Firepits
- Metals
- Wood
- Natural Stone

PROPERTIES

- Invisible/Natural-look finish
- Minimizes salt and freeze/thaw damage
- Interior/Exterior
- Makes paver maintenance easier

COVERAGE

COVERAGE	
Size	Sq. Ft.
1 gal	200 Sq. Ft.
5 gal	1,000 Sq. Ft.

USER TIPS

- Test in an inconspicuous area before starting the general application to ensure desired results and expected finish.
- Always follow paver manufacturer's sealing recommendations.
- If using on manufactured stone, ask dealer about cleaning and sealing procedures prior to application.
- Care should be taken for vertical surface application where runs may alter the finish.
- Always make sure surface is completely dry before applying sealer to ensure even coverage.
- Do not use more than one sealer on the same project.

SRW Products
800-752-9326

32005 126th St.
PO Box 70
Princeton, MN 55371

SRWProducts.com

Revised: 03-22-2021

PS Paver Seal™ Technical Data Sheet

Page 1 of 3

INSTALLATION INSTRUCTIONS

CLEAN

1. Wait 28 days after installing polymeric sand before sealing.
2. Thoroughly sweep surface of joint sand or loose material.
3. Spot clean if needed with one of the SRW Specialty Clean™ products. Then, prepare all pavers with a SRW Products General Purpose Cleaner.

CLIMATE

4. After cleaning, wait at least 24 hours before sealing. Surface and joints must be completely dry.
5. Recommended application temperatures are 50°F - 80°F (10°C - 27°C) from installation through the cure process.
6. Do not apply if inclement weather is forecasted within 24 hours.

APPLY

7. STIR THOROUGHLY.
8. Apply with an SRW Products approved Slit Foam Roller and sprayer.
9. For best results, spray then back roll. This prevents an uneven finish. A 2-person application is recommended.
10. Start at the highest project elevation. Do not allow sealer to pool on pavers or in joints.
11. Repeat if desired.

CURE

12. Allow sealed area to dry and cure 24 hours.
13. Protect area from water and rain until dry.

Dry-tack free: 25 minutes

Foot traffic: 24 hours

Vehicle traffic: 72 hours

Note: All calculations based on 68°F – 77°F (20°C – 25°C)

STORAGE AND SHELF LIFE

Keep from freezing. Store container in a cool area with cap or lid firmly in place.

CLEAN UP

Rinse off all equipment with soap and water and let dry.

WARNINGS

CAUTION: Protect buildings, landscaping and vehicles from overspray or spray drift.

WARNING: Do not inhale spray mist. Irritating to skin and eyes. Always wear a mask and protective eyewear and clothing. See SDS for further information.

IMPORTANT NOTICE: Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only. For professional use only. Test in a small, discrete area before use. **FIRST AID: EYES:** Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek medical attention.

SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing. **INGESTION:** If a large amount is ingested, give water or milk and induce vomiting. Seek

medical attention. **INHALATION:** Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

HMIS RATING: Hazard Index 2=moderate hazard, 0=minimal hazard

Health 2, Flammability 0, Reactivity 0, Protection G

IMPORTANT NOTICE: Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only. For professional use only. Test in a small, discrete area before use.

SHIPPING

DOT Shipping Name: Not Regulated.

PACKAGING

Paver Seal™ PS Penetrating			
PART #	SIZE	AMT PER CTN	QUANTITY
SSPSPLUS CTN	1 gal	4/CTN	36 CTNS/PLT
SSPSPLUS 5 GAL	5 gal	1	36/PLT

SRW Products

800-752-9326

32005 126th St.

PO Box 70

Princeton, MN 55371

SRWProducts.com

Revised: 03-22-2021

PS Paver Seal™ Technical Data Sheet

Page 3 of 3