
CALIBRATION (CONT)

- 7. When the zeroing process is complete the display will prompt for entry of the calibration weight. Minimum calibration is 200 lb / 100 kg. Maximum calibration weight is 1000 lb / 454 kg. Calibration weight can be adjusted in 10 lb or 10 kg increments. Press the calibration weight is set.
- 8. The display will prompt for the calibration weights to be placed on the platform. Press Enter after calibration weights are placed on the platform.
- 9. The display will show "Calibrating" during the calibration process.
- 10. If calibration is successful, the display will show "Calibration Complete" with a 4 digit calibration count.
- 11. If calibration is unsuccessful, the display will show an error message that the entered calibration weight and the certified weights do not match. The display will then revert back to the set calibration weight screen for entry of calibration weight.











TROUBLESHOOTING

Troubleshooting

Before contacting service personnel, refer to the following instructions to check and to correct any failures. For further assistance, contact Health o meter[®] Professional Scales Technical Support at 1-800-638-3722.

Symptom	Possible Cause	Corrective Action
Scale does not power on	Dead battery	1. Replace batteries
	2. Faulty electrical outlet	2. Use a different outlet
	3. Bad power supply	3. Replace AC adapter
Questionable weight or the scale does not zero	External object interfering with the scale	Remove interfering object from the scale
	2. The display did not show "0.0" before weighing	2. Remove the patient from the scale, press (Clear) to zero the scale and begin weighing process again
	Scale is not placed on a level floor or feet are not properly balanced	3. Place the scale on a level floor. Ensure all 4 feet are properly balanced. Completely hand tighten the feet, then turn them back 1-½ full turns.
	4. Scale is out of calibration	Check weight with known weight value
Weighing is performed but the weighing process takes too long and the weight does not lock on the display	The patient is not sitting or standing still	Ask the patient to stand or sit still
The battery icon on the display indicates that the batteries are low	The batteries are depleted	Replace batteries according to instructions on page 10
Scale is displaying "Load Cell Cable Not Detected"	The load cell cable is not completely plugged into the ports	Inspect the load cell cable to ensure it is completely plugged into the ports on the back of the display head and the back of the platform. See assembly instructions. If cable was plugged in, unplug and plug in again until it clicks into place.
In the Help menu, display is not advancing to the next screen for the menu selection and saying "invalid key"	Correct key is not being pressed	To make a selection in the Help Menu and advance the screen, press