



LITECHASER *PRO*

Model

iPhone 12 Pro / iPhone 12 Pro Max



What's Included

Filmmaking Kit

Phone Case | Wrist Tether | Grip | VND 3-5 Filter

Directors Kit

*Phone Case | Wrist Tether | Grip | VND 3-5
Mist 3-5 | Bluetooth Remote Shutter | CR2032 Battery | Hex Key*

Filters

Filter | Microfiber | Defender Filter Cover | Filter Hard Case

Grip

Grip

Phone Case

Phone Case | Wrist Tether

Bluetooth Remote Shutter

Bluetooth Remote Shutter | CR2032 Battery | Hex Key

Filter Installation

Step 1

Install phone in case and turn off flash.

Step 2

With camera side facing you, align upper and lower prongs of filter with the receiver slots on the case.

Step 3

Insert the filter prongs into the receiver slots until filter base is sitting flush with the case.

Step 4

Slide filter to the right to secure.

Filter Removal

Step 1

Slide filter to the left and pull filter out.

Filter Specs



| | iPhone 12 Circular Polarizer | iPhone 12 VND 3-5 Stop | | |
|------------------------------|--|----------------------------------|-----------------------|-----------------------|
| FILTER TYPE / STOP REDUCTION | CP 1.6 Stop | ND8 3 Stop | ND16 4 Stop | ND32 5 Stop |
| OUTSIDE DIAMETER | <i>53.25mm x 7mm</i> | <i>53.25mm x 7mm</i> | | |
| WEIGHT | <i>14.72g</i> | <i>20.03g</i> | | |

Filter Specs



| | iPhone 12 Mist | iPhone 12 Mist Diffusion 3-5 | | |
|------------------------------|--------------------------|--|-----------------------|-----------------------|
| FILTER TYPE / STOP REDUCTION | MIST 0.51 Stop | ND8 3 Stop | ND16 4 Stop | ND32 5 Stop |
| OUTSIDE DIAMETER | <i>53.25mm x 7mm</i> | <i>53.25mm x 7mm</i> | | |
| WEIGHT | <i>14.72g</i> | <i>20.03g</i> | | |

Grip Installation

Step 1

Make sure case is installed on phone.

Step 2

Choose desired side (front of case / back of case)

Step 3

Attach grip by sliding the switch upwards and pressing down to release locking ends of the grip.

Step 4

Place locking ends on one of the four predetermined rail system grooves located on the side of the case and release the grip switch.

Grip Installation (Continued)

Step 4

Ensure locking ends of the grip are secure by squeezing the edges. Make sure the grip is level and tight against the case and double-check that the red indicator isn't showing on the Grip switch.

- *To remove, repeat Step 3 and detach.*

Bluetooth Module Installation

Step 1

Start by opening the rubber flap located on top of the module to access the top screw.

Step 2

Align the module's top screw with the LiteChaser Grip ¼"-20 and begin threading the screw with the included hex key until the module is tightened firmly against the grip.

Step 3

Press down on the rubber flap until it's securely into place.

Bluetooth Remote Shutter On / Off

Step 1

Simply switch the toggle to turn on bluetooth connection. A green light will illuminate when powered on.

Step 2

To connect, locate the bluetooth settings on your mobile device and connect to LCP-BT-SHUTTER.

Step 3

Once connected the light located on the module will flash for both photo and video when the shutter is engaged.

More Info

Tutorials

For additional help be sure to visit our YouTube page:

[youtube.com/polarprofilers](https://www.youtube.com/polarprofilers)

for tutorials and more.

Questions

Contact us at anytime via our website, or shoot us an email. We're happy to help.

polarpro.com | 949.220.9395

support@polarpro.com