

# Fire Extinguishers



**MED APPROVED**  
EXTINGUISHERS

**ABC Powder**

**MEDIUM** ABC 40 Dry Powder

**TYPE** Stored Pressure

**PROPELLANT** Nitrogen

**OPERATING PRESSURE** 15 Bar (at 20°C)

**TEST PRESSURE** 27 Bar (EPS2 25 Bar)

✓ Quality deep drawn cylinders  
(4, 6 & 9kg models only)

✓ High quality heavy-duty brass valves

✓ Colour coded handles and bases



Approved to Marine Equipment Directive 96/98 EC | Colour Coded |



## Product Specifications

EXTINGUISHER	2kg ABC Powder	4kg ABC Powder	6kg ABC Powder	9kg ABC Powder
PRODUCT CODE	EPS2MED	EPS4MED	EPS6MED	EPS9MED
CAPACITY	2kg	4kg	6kg	9kg
FIRE RATING	13A   70B   C	21A   113B   C	27A   183B   C	43A   233B   C
OPERATING TEMPERATURE	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C
AVERAGE DISCHARGE TIME	9.5 seconds	12.9 seconds	16.1 seconds	16.7 seconds
HEIGHT	391mm	411mm	517mm	552mm
DIAMETER	108mm	160mm	160mm	189mm
FILLED WEIGHT	3.2kg	6.95kg	9.55kg	13.6kg
EMPTY WEIGHT	1.2kg	2.9kg	3.5kg	4.5kg
PACKING SPEC (HxWxD)	393 x 159 x 117mm	415 x 175 x 175mm	529 x 177 x 177mm	549 x 205 x 205mm
REFILL PART NUMBER	See page 37	See page 37	See page 37	See page 37