Radio control model **R/C Flugmodell INSTRUCTION MANUAL** MONTAGEANLEITUNG



Designed for brushless electric motors (.46-.52 class glow conversion optional) Entwickelt für Brushless Elektro Motoren (7,5 -8,5cc Glühzündermotor Einbau möglich)



TECHNISCHE DATEN

Spannweite Länge Elektroantrieb Verbrennerantrieb Fernsteuerung

1620mm 1210mm (siehe nächste Seite) 7.5cc 2-T / 8.5cc 4-T 6 Kanal / 6-7 Servos Wingspan Length Electric Motor Glow Engine Radio

63 in. 47.6 in. (See next page) .46 2Stroke / .52 4-Stroke 6 Channel / 6-7 Servos

WARNING! This radio controlled model is NOT a toy. If modified or flown carelessly it could go out of controll and cause serious human injury or property damage. Before flying your airplane, ensure the air field is spacious enough. Always fly it outdoors in safe areas and seek professional advice if you are unexperienced.

ACHTUNG! Dieses ferngesteuerte Modell ist KEIN Spielzeug! Es ist für fortgeschrittene Modellflugpiloten bestimmt, die ausreichende Erfahrung im Umgang mit derartigen Modellen besitzen Bei unsachgemäßer Verwendung kann hoher Personen- und/oder Sachschaden entstehen. Fragen Sie in einem Modellbauverein in Ihrer Nähe um professionelle Unterstützung, wenn Sie Hilfe im Bau und Betrieb benötigen. Der Zusammenbau dieses Modells ist durch die vielen Abbildungen selbsterklärend und ist für fortgeschrittene, erfahrene Modellbauer bestimmt.







Push the rudder and its hinges into the hinge slots in the trailing edge of the horizontal stabilizer. There should be a minimal hinge gap. When satisfied with the and alignment, hinge the elevator to the horizontal stabilizer using CA glue.





DORNIER DO-27 8- Electric motor



Plywood moto



Rudder servo (mini servo)

FUSELAGE - BOTTOM VIEW

FUSELAGE - BOTTOM VIEW

The holes for the rudder servo are Pre-cut at factory (left and right side of the fuselage). Cut away only the covering





DORNIER DO-27 15- Decor



Note: Cut out the stickers and apply them in the proper area. Do not peel the backing paper off all at once.

Peel off one corner of the backing and cut off with scissors.

Arrange sticker on model and when satisfied adhere the corner without backing.

Carefully peel back the rest of the backing while at the same time adhering the rest of the sticker.

Try not to make air bubbles, if there are some, carefully puncture sticker (center of bubble) but not model surface with the tip

of the knife or sharp pin and squeeze out the air. At curves stretch sticker and apply a little heat so that no ceases occur.

Cut off the excess that is produced.

IMPORTANT: Please do not clean your model with pure alcohol, only use liquid soap with water or use glass cleaner to clean on surface of your model to keep the colour not fade.



IMPORTANT: Flying your model at these throws will provide you with the greatest chance for successful first flights. If,after you have become accustomed to the way the Spitfire flies, you would like to change the throws to suit your taste that is fine. However, too much control throw could make the model difficult to control, so remember, "more is not always better".