



Range: 4000 Kg - 8000 Kg

Plus:

- Sideshifting heavy-duty fork positioner with bar mounted forks.
- Integral sideshift.
- ISO 2328 mounting to the lift truck carriage.
- Built-in sideshift improves handling.

03

Model	Capacity kg	Load Centre		Opening Range mm	Fork Length x Section mm	Sideshift Stroke mm	Frame Width mm	Minimum Carriage Width mm	Height mm	Weight Kg	Horizontal Centre of Gravity mm	Vertical Centre of Gravity mm	Effective Thickness mm	Mounting Class ISO 2328	Price €
		BP	B												
SF40F12	4.000	600	370-1.070	1.200X125X50	①	1.200	1.000	793	457	154	320	185	3 A	7.690	
SF40F13	4.000	600	370-1.170	1.200X125X50	①	1.300	1.000	793	468	153	324	185	3 A	7.890	
SF40F14	4.000	600	370-1.270	1.200X125X50	①	1.400	1.000	793	479	150	326	185	3 A	8.080	
SF40F15	4.000	600	370-1.370	1.200X125X50	①	1.500	1.000	793	490	148	330	185	3 A	8.270	
SF40F16	4.000	600	370-1.470	1.200X125X50	①	1.600	1.000	793	502	146	334	185	3 A	8.530	
Forks: Max. length 1600 mm. Add-on price per each 100 mm length increase															170
SF50F14	5.000	600	410-1.270	1.200x150x50	①	1.400	1.000	844	520	167	367	185	4 A	9.280	
SF50F15	5.000	600	410-1.370	1.200x150x50	①	1.500	1.000	844	532	165	371	185	4 A	9.510	
SF50F16	5.000	600	410-1.470	1.200x150x50	①	1.600	1.000	844	544	162	374	185	4 A	9.720	
SF50F17	5.000	600	410-1.570	1.200x150x50	①	1.700	1.000	844	554	160	377	185	4 A	9.920	
SF50F18	5.000	600	410-1.670	1.200x150x50	①	1.800	1.000	844	565	158	379	185	4 A	10.130	
Forks: Max. length 1600 mm. Add-on price per each 100 mm length increase															190
SF70F18	7.000	600	480-1.620	1.200x150x60	①	1.800	1.000	862	753	132	411	215	4 A	12.940	
SF70F19	7.000	600	480-1.720	1.200x150x60	①	1.900	1.000	862	771	131	414	215	4 A	13.190	
SF70F20	7.000	600	480-1.820	1.200x150x60	①	2.000	1.000	862	789	130	416	215	4 A	13.410	
SF70F21	7.000	600	480-1.920	1.200x150x60	①	2.100	1.000	862	806	129	419	215	4 A	13.690	
SF70F22	7.000	600	480-2.020	1.200x150x60	①	2.200	1.000	862	825	128	422	215	4 A	13.910	
Forks: Max. length 2000 mm. Add-on price per each 100 mm length increase															210
SF80F19	8.000	600	480-1.720	1.200x150x70	①	1.900	1.000	862	803	147	413	225	4 A	14.150	
SF80F20	8.000	600	480-1.820	1.200x150x70	①	2.000	1.000	862	821	144	416	225	4 A	14.330	
SF80F21	8.000	600	480-1.920	1.200x150x70	①	2.100	1.000	862	838	143	418	225	4 A	14.630	
SF80F22	8.000	600	480-2.020	1.200x150x70	①	2.200	1.000	862	857	141	420	225	4 A	14.860	
Forks: Max. length 2000 mm. Add-on price per each 100 mm length increase															250

Notes:

- Two hydraulic functions required.
 - ① Depending on fork opening position.
- Flow divider.

Options:

- Special widths.
- Non-sideshifting models.
- Load backrest.
- Models with fork adapters also available at same price (become SFxAxx).

3-37