



**Range:** 1600 Kg - 2000 Kg

**Plus:**

- Ideal for applications where pull function is not needed.
- Tilting push plate and quick-change hooks included.
- Strong, lightweight steel standard.

Model	Capacity	Load Centre	Platen Size	Platen Out-to-Out	Push Plate	Thickness	Horizontal Centre of Gravity	Vertical Centre of Gravity	Weight	Mounting Class
	<i>Q</i> kg	<i>BP</i> mm	<i>A x L</i> mm	<i>B</i> mm	<i>I x H</i> mm	<i>LL</i> mm	<i>HCG</i> mm	<i>VCG</i> mm	<i>W</i> Kg	<i>ISO</i> 2328
<b>Non-Sideshifting with Adjustable Platens, 1 Function</b>										
PL NH 035 A1548	1.600	600	380 x 1.200	865-1.065	1.000 x 1.010	190	295	206	473	2 A
PL NH 045 A1548	2.000	600	380 x 1.200	865-1.065	1.000 x 1.010	190	297	208	478	2 A
PL NH 045 B1548	2.000	600	380 x 1.200	865-1.065	1.000 x 1.010	239	320	249	542	3 A
<b>Sideshifting with Adjustable Platens, 2 Functions</b>										
PL SH 035 A1548	1.600	600	380 x 1.200	865-1.065	1.000 x 1.010	190	292	206	478	2 A
PL SH 045 A1548	2.000	600	380 x 1.200	865-1.065	1.000 x 1.010	190	295	208	482	2 A
PL SH 045 B1548	2.000	600	380 x 1.200	865-1.065	1.000 x 1.010	239	318	249	547	3 A

**Notes:**

- Hydraulic functions according to charts indication.