



Range: 5000 Kg - 8000 Kg

Plus:

- Heavy-duty fork positioner with separate sideshift.
- Pin-mounted forks.
- Integral mounting adapted to the lift truck. Minimum load distance ensures maximal residual lifting capacity.
- Built-in separate sideshift improves handling.

03

Model	Capacity		Load Centre	Opening Range	Fork Length x Section	Sideshift Stroke	Frame Width	Height	Weight	Horizontal Centre of Gravity	Vertical Centre of Gravity	Effective Thickness	Mounting Class	Price
	Q kg	BP mm												
SG50Fi14	5.000	600	410-1.270	1.200x150x50	150+150	1.400	895	523	200	365	160	①	11.680	
SG50Fi15	5.000	600	410-1.370	1.200x150x50	150+150	1.500	895	535	196	369	160	①	12.030	
SG50Fi16	5.000	600	410-1.470	1.200x150x50	150+150	1.600	895	547	192	373	160	①	12.170	
SG50Fi17	5.000	600	410-1.570	1.200x150x50	150+150	1.700	895	557	189	377	160	①	12.390	
SG50Fi18	5.000	600	410-1.670	1.200x150x50	150+150	1.800	895	568	188	380	160	①	12.840	
Forks: Max. length 1600 mm. Add-on price per each 100 mm length increase													190	
SG70Fi18	7.000	600	480-1.620	1.200x150x60	150+150	1.800	913	778	150	423	190	①	17.130	
SG70Fi19	7.000	600	480-1.720	1.200x150x60	150+150	1.900	913	796	148	426	190	①	17.390	
SG70Fi20	7.000	600	480-1.820	1.200x150x60	150+150	2.000	913	814	146	429	190	①	17.620	
SG70Fi21	7.000	600	480-1.920	1.200x150x60	150+150	2.100	913	831	145	432	190	①	17.810	
SG70Fi22	7.000	600	480-2.020	1.200x150x60	150+150	2.200	913	850	143	435	190	①	18.140	
Forks: Max. length 2000 mm. Add-on price per each 100 mm length increase													210	
SG80Fi19	8.000	600	480-1.720	1.200x150x70	150+150	1.900	913	818	178	425	200	①	18.310	
SG80Fi20	8.000	600	480-1.820	1.200x150x70	150+150	2.000	913	836	175	428	200	①	18.600	
SG80Fi21	8.000	600	480-1.920	1.200x150x70	150+150	2.100	913	853	173	431	200	①	18.820	
SG80Fi22	8.000	600	480-2.020	1.200x150x70	150+150	2.200	913	872	170	433	200	①	19.070	
Forks: Max. length 2000 mm. Add-on price per each 100 mm length increase													250	

Notes:

- Two hydraulic functions required.
 - ① Attachment price includes an integral mounting without mast rollers. A complete technical description of the mounting is required. Consult Bolzoni regarding specifications.
 - ② Weight and centre of gravity (vertical and horizontal) are given without the integral mounting.
- Flow divider.

Options:

- Special widths.
- Load backrest.
- Available also with fork adapter, at no add-on price (become SGxxAixx). Consult Bolzoni regarding specifications.