



Models AR-RT

Model	Capacity	Load Centre	Roll Range	Height	Weight	Centre of Gravity	Centre of Gravity	Effective Thickness	Contact Pads	Contact Pad Gap	Mounting Height	Mounting Class
	Q	BP	A	D	W	HCG	VCG	LL	M x N	O	H	ISO
	kg	mm	mm	mm	kg	mm	mm	mm	mm	mm	mm	2328
AR-22RT-16	1750	800	350-1600	1240	790	435	360	180	280x1200	-	265	2 / 3 A
AR-22RT-17	1600	850	400-1700	1240	810	450	360	180	280x1200	-	265	2 / 3 A
AR-22RT-18	1500	915	400-1830	1240	830	475	360	180	280x1200	-	265	2 / 3 A
AR-30RT-18	2500	915	400-1830	1240	910	385	360	200	280x1200	-	265	3 A
AR-30RT-19	2400	950	400-1900	1240	930	400	360	200	280x1200	-	265	3 A
AR-30RT-20	2250	1015	400-2030	1240	945	415	360	200	280x1200	-	265	3 A
AR-30RT-21	2100	1065	450-2130	1240	960	425	360	200	280x1200	-	265	3 A
AR-37RT-18	2800	915	450-1830	1440	1220	510	435	190	400x1400	-	285	3 / 4 A
AR-37RT-19	2650	950	500-1900	1440	1240	520	435	190	400x1400	-	285	3 / 4 A
AR-37RT-20	2500	1015	500-2030	1440	1270	540	435	190	400x1400	-	285	3 / 4 A
AR-37RT-21	2400	1050	600-2130	1440	1300	560	435	190	400x1400	-	285	3 / 4 A
AR-40RT-20	2900	1015	500-2030	1640	1480	520	435	210	400x1600	-	385	3 / 4 A
AR-40RT-21	2750	1065	600-2130	1640	1520	540	435	210	400x1600	-	385	3 / 4 A
AR-40RT-22	2650	1100	650-2200	1640	1560	570	435	210	400x1600	-	385	3 / 4 A
AR-40RT-23	2500	1150	800-2300	1640	1600	590	435	210	400x1600	-	385	3 / 4 A
AR-45RT-22	3050	1100	850-2200	1640	1630	550	395	212	400x1600	-	425	4 A
AR-45RT-23	2900	1150	850-2300	1640	1650	570	395	212	400x1600	-	425	4 A
AR-45RT-24	2750	1200	850-2400	1640	1680	590	395	212	400x1600	-	425	4 A
AR-45RT-25	2600	1270	850-2540	1640	1710	610	395	212	400x1600	-	425	4 A
AR-53RT-23	3250	1150	850-2300	1840	1870	570	520	240	400x1800	-	400	4 A
AR-53RT-24	3100	1200	850-2400	1840	1900	590	520	240	400x1800	-	400	4 A
AR-53RT-25	2950	1270	850-2540	1840	1930	610	520	240	400x1800	-	400	4 A
AR-60RT-23	3850	1150	850-2300	1840	2010	580	520	245	400x1800	-	400	4 A
AR-60RT-24	3700	1200	850-2400	1840	2040	600	520	245	400x1800	-	400	4 A
AR-60RT-25	3550	1270	850-2540	1840	2070	620	520	245	400x1800	-	400	4 A
RA-400-NLT	4000	1300	850-2600	1440	2240	500	530	260	700x1400	-	x	4 A / 5 A
RA-500-NLT	5000	1250	650-2500	1440	2150	480	530	260	700x1400	-	x	4 A / 5 A
RA-600-NLT	6000	1350	1500-2700	1840	3400	800	660	290	700x1800	-	x	x

Notes:

- Two hydraulic functions required.
- Consult Bolzoni for hydraulic pressure and flow rate recommendations. Standard contact pads: rubber faced, unsplit pads.
- For bilge handling, 5-degree forward tilt on upright is required.

Options:

- Special roll ranges.
- Special arms for 0-degree tilt.
- Contact pad options: plain pad surface.