



Models BA-RJ

Model	Capacity	Load Centre	Roll Range	Frame Width	Height	Weight	Centre of Gravity	Centre of Gravity	Effective Thickness	Contact Pads	Contact Pad Gap	Mounting Height	Mounting Class
	<i>Q</i>	<i>BP</i>	<i>A</i>	<i>C</i>	<i>D</i>	<i>W</i>	<i>HCG</i>	<i>VCG</i>	<i>LL1/LL2</i>	<i>M x N</i>	<i>O</i>	<i>H</i>	<i>ISO</i>
	<i>kg</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>kg</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>2328</i>
BA-50-RJ	5000	650	2x [915-1300]	1600	1240	1610	255	354	200/380	280x500	200	230	4 A
BA-50-LRJ	5000	675	2x [850-1350]	1600	1240	1630	260	354	200/380	280x500	200	230	4 A

Notes:

- Two hydraulic functions required.
- Consult Bolzoni for hydraulic pressure and flow rate recommendations.
- Standard contact pads: cast pad with high-friction surface.

Options:

- Special roll ranges.
- External sideshift.
- Independent arm movement.
- Fixed centre arm and two moveable split arms.
- Full-length contact pads.
- Contact pad options: steel-sprayed, polyutethane-faced, rubber faced, flexible.