



Models B-PU

Model	Capacity	Load Centre	Opening Range	Arm Length	Arm Height	Frame Width	Height	Weight	Centre of Gravity	Centre of Gravity	Effective Thickness	Mounting Height	Mounting Class
	<i>Q</i>	<i>BP</i>	<i>B</i>	<i>L</i>	<i>N</i>	<i>C</i>	<i>D</i>	<i>W</i>	<i>HCG</i>	<i>VCG</i>	<i>LL</i>	<i>H</i>	<i>ISO</i>
	<i>kg</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>kg</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>2328</i>
B-400PU-12RH1	4000	800	610-2190	1200	445	1400	825	1025	279	x	237	74	3 / 4 A
B-400PU-14RH1	4000	800	610-2170	1400	445	1400	825	1080	321	x	237	74	3 / 4 A
B-400PU-16RH1	4000	800	610-2160	1600	445	1400	825	1140	394	x	237	74	3 / 4 A
B-400PU-12RJ1	4000	800	710-2390	1200	445	1400	825	1045	276	x	237	74	3 / 4 A
B-400PU-14RJ1	4000	800	710-2370	1400	445	1400	825	1100	317	x	237	74	3 / 4 A
B-400PU-16RJ1	4000	800	710-2360	1600	445	1400	825	1160	390	x	237	74	3 / 4 A
B-400PU-12TH1	4000	800	610-2390	1200	445	1600	825	1050	273	x	237	74	3 / 4 A
B-400PU-14TH1	4000	800	610-2370	1400	445	1600	825	1100	314	x	237	74	3 / 4 A
B-400PU-16TH1	4000	800	610-2360	1600	445	1600	825	1165	387	x	237	74	3 / 4 A
B-400PU-12TJ1	4000	800	710-2590	1200	445	1600	825	1070	270	x	237	74	3 / 4 A
B-400PU-14TJ1	4000	800	710-2570	1400	445	1600	825	1120	311	x	237	74	3 / 4 A
B-400PU-16TJ1	4000	800	710-2560	1600	445	1600	825	1185	382	x	237	74	3 / 4 A
B-400PU-12VH1	4000	800	610-2590	1200	445	1800	825	1090	264	x	237	74	3 / 4 A
B-400PU-14VH1	4000	800	610-2570	1400	445	1800	825	1140	304	x	237	74	3 / 4 A
B-400PU-16VH1	4000	800	610-2560	1600	445	1800	825	1210	374	x	237	74	3 / 4 A
B-400PU-12VJ1	4000	800	710-2790	1200	445	1800	825	1110	261	x	237	74	3 / 4 A
B-400PU-14VJ1	4000	800	710-2770	1400	445	1800	825	1165	301	x	237	74	3 / 4 A
B-400PU-16VJ1	4000	800	710-2760	1600	445	1800	825	1230	370	x	237	74	3 / 4 A

Notes:

- Two hydraulic functions.

Options:

- Special opening ranges.