



Models KG-G

Model	Capacity	Load Centre	Opening Range	Arm Dimensions	Frame Width	Minimum Carriage Width	Rotator Height	Weight	Centre of Gravity	Centre of Gravity	Effective Thickness	Side Visibility	Ground Clearance	Arm Toe-in	Mounting Class
	Q kg	BP mm	B mm	LxAxE-T mm	I mm	FL mm	D1 mm	W kg	HCG mm	VCG mm	LL mm	U mm	P mm	C mm	ISO 2328
KG 10 G2A-58-181	1000	500	580-1810	700x400x25-45	930	580	730	425	228	257	231	337	6	19	2 A
KG 10 G4A-58-181	1000	500	580-1810	1000x400x30-45	930	580	730	468	315	246	231	337	6	24	2 A
KG 10 G6A-58-181	1000	500	580-1810	1200x400x30-45	930	580	730	496	367	242	231	337	6	29	2 A
KG 14 G2A-58-181	1400	500	580-1810	700x400x25-45	930	580	730	425	228	257	231	337	6	19	2 A
KG 14 G4A-58-181	1400	500	580-1810	1000x400x30-45	930	580	730	468	315	251	231	337	6	24	2 A
KG 14 G6A-58-181	1400	500	580-1810	1200x400x30-45	930	580	730	496	367	242	231	337	6	29	2 A
KG 18 G4A-64-197	1800	500	640-1970	1000x400x30-45	970	580	730	528	306	246	231	336	9	25	2 A
KG 18 G6A-64-197	1800	500	640-1970	1200x400x30-45	970	580	730	522	356	242	231	336	9	29	2 A
KG 18 GXA-64-197	1800	500	640-1970	1600x400x35-45	970	580	730	574	475	234	231	336	9	39	2 A
KG 22 G4A-64-197	2200	500	640-1970	1000x400x30-45	970	580	730	528	306	246	231	336	9	25	2 A
KG 22 G6A-64-197	2200	500	640-1970	1200x400x30-45	970	580	730	523	356	242	231	336	9	29	2 A
KG 22 GXA-64-197	2200	500	640-1970	1600x400x35-45	970	580	730	574	475	234	231	336	9	39	2 A
KG 25 G4B-64-237	2500	500	640-2370	1000x400x35-50	1370	870	844	675	288	297	241	428	20	23	3 A
KG 25 G6B-64-237	2500	500	640-2370	1200x400x35-50	1370	870	844	707	332	290	241	428	20	29	3 A
KG 25 GXB-64-237	2500	500	640-2370	1600x400x35-50	1370	870	844	778	433	279	241	428	20	39	3 A
KG 32 G4B-50-185	3200	600	500-1850	1000x450x40-70	1200	870	863	852	317	298	262	455	6	17	3 A
KG 32 G6B-50-185	3200	600	500-1850	1200x450x40-70	1200	870	863	893	326	287	262	455	6	21	3 A
KG 32 G4B-50-195	3200	600	500-1950	1000x450x40-70	1280	870	863	877	311	301	262	455	6	17	3 A
KG 32 G6B-50-195	3200	600	500-1950	1200x450x40-70	1280	870	863	919	318	291	262	455	6	21	3 A
KG 32 G4B-59-213	3200	600	590-2130	1000x450x40-70	1280	870	863	885	312	297	262	455	6	17	3 A
KG 32 G6B-59-213	3200	600	590-2130	1200x450x40-70	1280	870	863	942	344	294	262	455	6	21	3 A
KG 32 G4B-64-237	3200	600	640-2370	1000x450x40-70	1420	870	863	917	317	307	262	455	6	17	3 A
KG 32 G6B-64-237	3200	600	640-2370	1200x450x40-70	1420	870	863	991	338	297	262	455	6	21	3 A
KG 32 G8B-64-237	3200	600	640-2370	1500x450x45-75	1420	870	863	1058	464	265	262	455	6	26	3 A
KG 40 G4B-53-198	4000	600	530-1980	1000x450x45-70	1250	870	859	942	341	261	272	450	0	18	3 A
KG 40 G6B-53-198	4000	600	530-1980	1200x450x45-70	1250	870	859	981	382	258	272	450	0	21	3 A
KG 40 G4B-59-213	4000	600	590-2130	1000x450x45-70	1280	870	859	956	327	267	272	450	0	18	3 A
KG 40 G6B-59-213	4000	600	590-2130	1200x450x45-70	1280	870	859	995	372	260	272	450	0	21	3 A
KG 40 G4B-60-237	4000	600	600-2370	1000x450x45-70	1500	870	859	992	322	272	272	450	0	18	3 A
KG 40 G6B-60-237	4000	600	600-2370	1200x450x45-70	1500	870	859	1036	369	261	272	450	0	21	3 A

KG 40 GXB-60-237	4000	600	600-2370	1600x450x40-65	1500	870	859	1176	489	251	272	450	0	28	3 A
KG 40 G4B-74-264	4000	600	740-2640	1000x450x45-70	1590	870	859	1014	319	272	272	450	0	18	3 A
KG 40 G6B-74-264	4000	600	740-2640	1200x450x45-70	1590	870	859	1059	364	263	272	450	0	21	3 A
KG 40 GXB-74-264	4000	600	740-2640	1600x450x40-65	1590	870	859	1215	451	285	272	450	0	28	3 A

Notes:

- Two hydraulic functions.
- Capacity during rotation depends on the clamping pressure and on the load.
- Pressure relief valve.
- Rotating centre.
- Double check valve.
- Arms welded directly to the guides.

Options:

- Special openings.
- Separate sideshift:
- ISO 2328 2
- ISO 2328 3
- Quick change lower hooks.
- Pressure gauge.
- Load backrest.
- Arms of various dimensions.