



**Models RA-180**

Model	Capacity	Load Centre	Roll Range	Height	Weight	Centre of Gravity	Centre of Gravity	Effective Thickness	Contact Pads	Contact Pad Gap	Mounting Height	Mounting Class
	<i>Q</i>	<i>BP</i>	<i>A</i>	<i>D</i>	<i>W</i>	<i>HCG</i>	<i>VCG</i>	<i>LL</i>	<i>M x N</i>	<i>O</i>	<i>H</i>	<i>ISO</i>
	<i>kg</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>kg</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>2328</i>
<b>Single roll clamps - Unsplit long arm</b>												
RA-180-N	1800	650	250-1300	830	570	250	365	180	220x300	200	55	2 / 3 A
RA-180-NS	1800	550	250-1100	830	555	230	365	180	220x300	200	55	2 / 3 A
<b>1 - 2 roll clamps - Split long arm</b>												
RA-150-NLJ	1500	850	250-1700	830	610	295	365	180	220x300	200	55	2 / 3 A
RA-180-NJ	1800	650	250-1300	830	560	240	365	180	220x300	200	55	2 / 3 A
RA-180-NSJ	1800	550	250-1100	830	545	220	365	180	220x300	200	55	2 / 3 A

**Notes:**

- Two hydraulic functions.
- Consult Bolzoni for hydraulic pressure and flow rate recommendations.
- Standard contact pads: cast pad with a high-friction surface.
- For bilge handling, 5-degree forward tilt on upright is required.
- For 0-degree tilt, special arms are available. Consult Bolzoni.

**Options:**

- Special roll ranges.
- Contact pad options: steel-sprayed, rubber faced, polyurethane faced or flexible, full length contact pads.