



Range: 1000 Kg - 1800 Kg

Plus:

- Strong double T-profile frame.
- Reduced weight, effective thickness and centre of gravity.
- Excellent visibility.
- Used to handle large and light blocks of rubber or polystyrene.
- Light tubular profile arms, to guarantee a good support and avoid damage to loads.

| Model | Code | Capacity | Load Centre | Opening Range | Arm Dimensions | Frame Width | Minimum Carriage Width | Height | Weight | Horizontal Centre of Gravity | Vertical Centre of Gravity | Effective Thickness | Ground Clearance | Arm Height from Ground | Mounting Class |
|-----------|--------|----------|-------------|---------------|----------------|-------------|------------------------|--------|--------|------------------------------|----------------------------|---------------------|------------------|------------------------|----------------|
| | | Q kg | BP mm | B mm | LxAxE mm | I mm | FL mm | D mm | W Kg | HCG mm | VCG mm | LL mm | P mm | mm | ISO 2328 |
| KB 10 N8A | 80-225 | 1.000 | 500 | 800-2.250 | 1.500x550x70 | 1.160 | 690 | 625 | 288 | 258 | 260 | 152 | 9 | 30 | 2 A |
| KB 10 N9A | 80-225 | 1.000 | 500 | 800-2.250 | 1.800x550x70 | 1.160 | 690 | 625 | 303 | 318 | 260 | 152 | 9 | 30 | 2 A |
| KB 10 N0A | 80-225 | 1.000 | 500 | 800-2.250 | 2.000x550x70 | 1.160 | 690 | 625 | 318 | 423 | 260 | 152 | 9 | 30 | 2 A |
| KB 10 N8A | 75-236 | 1.000 | 500 | 750-2.360 | 1.500x550x70 | 1.370 | 690 | 625 | 313 | 258 | 260 | 152 | 9 | 30 | 2 A |
| KB 10 N9A | 75-236 | 1.000 | 500 | 750-2.360 | 1.800x550x70 | 1.370 | 690 | 625 | 328 | 318 | 260 | 152 | 9 | 30 | 2 A |
| KB 10 N0A | 75-236 | 1.000 | 500 | 750-2.360 | 2.000x550x70 | 1.370 | 690 | 625 | 338 | 423 | 260 | 152 | 9 | 30 | 2 A |
| KB 14 N8A | 80-225 | 1.400 | 500 | 800-2.250 | 1.500x550x70 | 1.160 | 690 | 625 | 298 | 258 | 260 | 152 | 9 | 30 | 2 A |
| KB 14 N9A | 80-225 | 1.400 | 500 | 800-2.250 | 1.800x550x70 | 1.160 | 690 | 625 | 313 | 318 | 260 | 152 | 9 | 30 | 2 A |
| KB 14 N0A | 80-225 | 1.400 | 500 | 800-2.250 | 2.000x550x70 | 1.160 | 690 | 625 | 328 | 423 | 260 | 152 | 9 | 30 | 2 A |
| KB 14 N8A | 87-260 | 1.400 | 500 | 870-2.600 | 1.500x550x70 | 1.370 | 690 | 625 | 331 | 227 | 260 | 152 | 9 | 30 | 2 A |
| KB 14 N9A | 87-260 | 1.400 | 500 | 870-2.600 | 1.800x550x70 | 1.370 | 690 | 625 | 406 | 310 | 260 | 152 | 9 | 30 | 2 A |
| KB 14 N0A | 87-260 | 1.400 | 500 | 870-2.600 | 2.000x550x70 | 1.370 | 690 | 625 | 421 | 360 | 260 | 152 | 9 | 30 | 2 A |
| KB 18 N8A | 87-260 | 1.800 | 500 | 870-2.600 | 1.500x550x70 | 1.370 | 690 | 654 | 392 | 253 | 301 | 160 | 9 | 30 | 2 A |
| KB 18 N9A | 87-260 | 1.800 | 500 | 870-2.600 | 1.800x550x70 | 1.370 | 690 | 654 | 414 | 332 | 301 | 160 | 9 | 30 | 2 A |
| KB 18 N0A | 87-260 | 1.800 | 500 | 870-2.600 | 2.000x550x70 | 1.370 | 690 | 654 | 430 | 382 | 301 | 160 | 9 | 30 | 2 A |

Notes:

- One hydraulic function required.
- Check valve with power regeneration hydraulic circuit.
- Pressure relief valve.

Options:

- Special openings.
- Separate sideshift.
- Integral sideshift.
- Quick change lower hooks.
- Pressure gauge.
- Load backrest.
- Custom built arm dimensions.