



Range: 1600 Kg - 10000 Kg

Plus:

- To hydraulically adjust the spacing of the forks inside and outside the truck width.
- Adjusted from the drivers position in seconds for each load or pallet size it is especially useful for lifting wide loads.

03

Model	Capacity	Load Centre	Chassis Width	Opening Range Over Forks	Fork Section	Fork Length	Center of Gravity Vertical	Fork Upright	Lost Load Centre	Horizontal Centre of Gravity	Weight	Mounting Class	Price
	Q kg	lc mm	A mm	F mm	KxH mm	L mm	Ev mm	D mm	C mm	Eh mm	M kg	ISO 2328	€
6-0116G-EU - a	1.600	500	870	250 - 1.200	100x35	1.200	178	35	123	209	258	2 A	6.220
6-0116G-EU - b	1.600	500	870	350 - 1.400	100x35	1.200	180	35	123	206	260	2 A	6.400
6-0116G-EU - c	1.600	500	970	250 - 1.300	100x35	1.200	181	35	123	201	248	2 A	6.510
6-0116G-EU - d	1.600	500	970	350 - 1.500	100x35	1.200	183	35	123	198	254	2 A	6.590
6-0116G - e	1.600	500	970	450 - 1.700	100x35	1.200	184	35	123	196	258	2 A	6.610
6-0116G-EU - f	1.600	500	1.050	350 - 1.580	100x35	1.200	185	35	123	194	260	2 A	6.770
6-0116G-EU - g	1.600	500	1.160	350 - 1.690	100x35	1.200	187	35	123	190	265	2 A	6.770
6-0116G - h	1.600	500	1.260	450 - 1.990	100x35	1.200	188	35	123	187	272	2 A	6.800
Additional price per 100 mm fork length up to 1800 mm.													110
6-0122G-EU - a	2.200	500	870	220 - 1.180	120x40	1.200	169	40	132	233	285	2 A	6.950
6-0122G-EU - b	2.200	500	870	320 - 1.380	120x40	1.200	171	40	132	229	292	2 A	7.050
6-0122G-EU - c	2.200	500	970	220 - 1.280	120x40	1.200	172	40	132	224	297	2 A	7.270
6-0122G-EU - d	2.200	500	970	320 - 1.480	120x40	1.200	174	40	132	223	304	2 A	7.430
6-0122G-EU - e	2.200	500	1.100	220 - 1.410	120x40	1.200	175	40	132	216	317	2 A	7.600
6-0122G-EU - f	2.200	500	1.100	320 - 1.610	120x40	1.200	177	40	132	215	318	2 A	7.670
6-0122G-EU - g	2.200	500	1.200	220 - 1.510	120x40	1.200	178	40	132	210	320	2 A	7.800
6-0122G-EU - h	2.200	500	1.200	320 - 1.710	120x40	1.200	179	40	132	210	320	2 A	7.870
6-0122G - i	2.200	500	1.270	420 - 1.980	120x40	1.200	180	40	132	208	325	2 A	8.350
Additional price per 100 mm fork length up to 1800 mm.													120
6-0125G-EU - a	2.200	600	870	220 - 1.180	120x45	1.200	164	45	132	250	301	2 A	7.710
6-0125G-EU - b	2.200	600	870	320 - 1.380	120x45	1.200	165	45	132	246	307	2 A	7.840
6-0125G-EU - c	2.200	600	970	220 - 1.280	120x45	1.200	166	45	132	240	310	2 A	8.120
6-0125G-EU - d	2.200	600	970	320 - 1.480	120x45	1.200	166	45	132	240	311	2 A	8.220
6-0125G-EU - e	2.200	600	1.100	220 - 1.410	120x45	1.200	167	45	132	233	332	2 A	8.490
6-0125G-EU - f	2.200	600	1.100	320 - 1.610	120x45	1.200	170	45	132	232	334	2 A	8.580
6-0125G-EU - g	2.200	600	1.200	320 - 1.510	120x45	1.200	174	45	132	228	350	2 A	8.690
6-0125G-EU - h	2.200	600	1.200	320 - 1.710	120x45	1.200	177	45	132	220	355	2 A	8.790
6-0125G - i	2.200	600	1.270	420 - 1.980	120x45	1.200	180	45	132	219	370	2 A	9.030
Additional price per 100 mm fork length up to 1800 mm.													120
6-0128G-EU - a	2.800	500	970	220 - 1.280	120x45	1.200	215	45	132	239	329	3 A	8.220
6-0128G-EU - b	2.800	500	970	320 - 1.480	120x45	1.200	220	45	132	235	330	3 A	8.280
6-0128G-EU - c	2.800	500	1.100	220 - 1.410	120x45	1.200	223	45	132	225	350	3 A	8.550
6-0128G-EU - d	2.800	500	1.100	320 - 1.610	120x45	1.200	225	45	132	224	354	3 A	8.610
6-0128G-EU - e	2.800	500	1.200	220 - 1.510	120x45	1.200	228	45	132	219	362	3 A	8.780
6-0128G-EU - f	2.800	500	1.200	320 - 1.710	120x45	1.200	230	45	132	218	365	3 A	8.810
6-0128G-EU - g	2.800	500	1.270	220 - 1.580	120x45	1.200	235	45	132	214	375	3 A	8.930
6-0128G-EU - h	2.800	500	1.270	320 - 1.780	120x45	1.200	236	45	132	213	379	3 A	8.990
6-0128G - i	2.800	500	1.370	420 - 2.080	120x45	1.200	238	45	132	202	406	3 A	9.620
Additional price per 100 mm fork length up to 1800 mm.													120
6-0135G-EU - a	3.500	500	970	220 - 1.280	120x50	1.200	212	50	132	233	358	3 A	9.360
6-0135G-EU - b	3.500	500	970	320 - 1.480	120x50	1.200	215	50	132	234	361	3 A	9.530
6-0135G-EU - c	3.500	500	1.100	220 - 1.410	120x50	1.200	218	50	132	239	366	3 A	9.680
6-0135G-EU - d	3.500	500	1.100	320 - 1.610	120x50	1.200	221	50	132	238	368	3 A	9.770

Model	Capacity	Load Centre	Chassis Width	Opening Range Over Forks	Fork Section	Fork Length	Center of Gravity Vertical	Fork Upright	Lost Load Centre	Horizontal Centre of Gravity	Weight	Mounting Class	Price
	Q	lc	A	F	KxH	L	Ev	D	C	Eh	M	ISO 2328	€
	kg	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg		
6-0135G-EU - e	3.500	500	1.200	220 - 1.510	120x50	1.200	225	50	132	234	388	3 A	9.930
6-0135G-EU - f	3.500	500	1.200	320 - 1.710	120x50	1.200	227	50	132	225	393	3 A	10.100
6-0135G-EU - g	3.500	500	1.260	220 - 1.570	120x50	1.200	229	50	132	221	408	3 A	10.150
6-0135G-EU - h	3.500	500	1.260	320 - 1.770	120x50	1.200	235	50	132	220	412	3 A	10.180
6-0135G-EU - i	3.500	500	1.370	220 - 1.680	120x50	1.200	238	50	132	216	432	3 A	10.800
6-0135G - j	3.500	500	1.370	420 - 2.080	120x50	1.200	240	50	132	215	436	3 A	10.890
Additional price per 100 mm fork length up to 1800 mm.													
6-0140G-EU - a	4.000	500	1.200	260 - 1.540	150x50	1.200	229	50	155	231	630	3 A	10.630
6-0140G-EU - b	4.000	500	1.280	260 - 1.620	150x50	1.200	230	50	155	228	639	3 A	10.820
6-0140G - c	4.000	500	1.280	460 - 2.020	150x50	1.200	234	50	155	227	644	3 A	11.230
6-0140G-EU - d	4.000	500	1.420	260 - 1.760	150x50	1.200	236	50	155	221	650	3 A	11.250
6-0140G - e	4.000	500	1.420	460 - 2.160	150x50	1.200	237	50	155	220	654	3 A	11.320
Additional price per 100 mm fork length up to 1800 mm.													
6-0142G-EU - a	4.200	600	1.150	260 - 1.490	150x60	1.200	229	60	165	241	602	3 A	12.060
6-0142G-EU - b	4.200	600	1.250	260 - 1.590	150x60	1.200	233	60	165	238	622	3 A	12.550
6-0142G - c	4.200	600	1.250	460 - 1.960	150x60	1.200	234	60	165	237	626	3 A	13.000
6-0142G-EU - d	4.200	600	1.500	260 - 1.840	150x60	1.200	234	60	165	227	668	3 A	13.320
6-0142G - e	4.200	600	1.500	460 - 2.240	150x60	1.200	238	60	165	225	676	3 A	13.390
Additional price per 100 mm fork length up to 1800 mm.													
Generation K / N													
6-0110K-EU - a	4.500	600	1.350	260 - 1.730	150x60	1.200	253	60	177	200	795	4 A	13.320
6-0110K - b	4.500	600	1.350	410 - 2.030	150x60	1.200	254	60	177	205	810	4 A	13.380
6-0110K-EU - c	4.500	600	1.500	260 - 1.880	150x60	1.200	258	60	177	190	840	4 A	13.630
6-0110K - d	4.500	600	1.500	410 - 2.180	150x60	1.200	259	60	177	190	850	4 A	13.690
6-0110K-EU - e	4.500	600	1.650	260 - 2.030	150x60	1.200	263	60	177	200	900	4 A	14.000
6-0110K - f	4.500	600	1.650	410 - 2.330	150x60	1.200	264	60	177	200	920	4 A	14.050
Additional price per 100 mm fork length up to 1800 mm.													
6-0111K-EU - a	6.000	600	1.350	260 - 1.730	150x65	1.200	255	65	177	210	860	4 A	13.850
6-0111K-EU - b	6.000	600	1.500	260 - 1.880	150x65	1.200	258	65	177	210	890	4 A	13.920
6-0111K-EU - c	6.000	600	1.650	260 - 2.030	150x65	1.200	259	65	177	190	900	4 A	14.230
Additional price per 100 mm fork length up to 1800 mm.													
6-0114K-EU - a	7.000	600	1.650	260 - 2.030	150x70	1.200	282	70	177	220	1.000	4 A	16.220
6-0114K - b	7.000	600	1.800	410 - 2.480	150x70	1.200	283	70	177	210	1.050	4 A	16.310
6-0114K-EU - c	7.000	600	1.950	260 - 2.330	150x70	1.200	288	70	177	200	1.100	4 A	16.780
6-0114K - d	7.000	600	1.950	410 - 2.630	150x70	1.200	289	70	177	200	1.150	4 A	17.140
Additional price per 100 mm fork length up to 1800 mm.													
6-0118N-EU - a	8.000	600	1.950	260 - 2.330	150x70	1.200	290	70	207	210	1.350	4 A	19.180
6-0118N - b	8.000	600	1.950	410 - 2.630	150x70	1.200	291	70	207	200	1.400	4 A	19.600
Additional price per 100 mm fork length up to 1800 mm.													
6-0120N - a	10.000	600	1.950	360 - 2.630	200x70	1.200	304	70	207	230	1.450	4 A	26.750
6-0120N - b	10.000	600	1.950	460 - 2.830	200x70	1.200	305	70	207	220	1.500	4 A	27.900
Additional price per 100 mm fork length up to 1800 mm.													
240													

03

Notes:

- Two hydraulic functions required.
- With integral sideshift.
- Forks welded to the slide bars.
- Pressure relief valve on opening and closing.
- EU models for Europallet handling.

Options:

- Additional cost for:
- Separate, built-on sideshift:
 ISO II, +/- 100 mm..... € 1.040
 (from chassis width A=970)
 ISO III, +/- 100 mm..... € 1.500
 ISO IV, +/- 100 mm.....contact Bolzoni
- Load backrest
- Quick disconnect lower hooks:
 ISO II/III. € 700
 ISO IV on request

- Design with bolt-on forks, (increase in C, E and M):
 ISO II..... € 790
 ISO III € 900
 ISO IV..... € 1.260
- Price reduction for ISO II + III without integral sideshift..... € 520