



Range: 1800 Kg - 5000 Kg

Plus:

- Strong double T-profile frame.
- Reduced weight, effective thickness and centre of gravity.
- Excellent visibility.
- Special harbour forks bolted on the arm carriers.

Model	Capacity	Load Centre	Opening Range	Fork Dimensions	Frame Width	Minimum Carriage Width	Height	Weight	Horizontal Centre of Gravity	Vertical Centre of Gravity	Effective Thickness	Side Visibility	Central Visibility	Ground Clearance	Mounting Class
	Q1/Q2 kg	BP mm	B mm	LxAxE mm	I mm	FL mm	D mm	W Kg	HCG mm	VCG mm	LL mm	U mm	V mm	P mm	ISO 2328
KB 18 P6A	1.800 / 2.500	500	490 - 1.820	1.200x120x40	970	690	613	348	220	162	195	340	197	9	2 A
KB 18 P6A EU	1.800 / 2.500	500	320 - 1.610	1.200x120x40	1.100	690	613	354	215	172	195	340	197	9	2 A
Forks: max. length 1.800 mm. Add-on price per each 100 mm length increase.															
KB 22 P6A	2.200 / 2.500	500	490 - 1.820	1.200x120x40	970	690	613	365	226	162	197	338	195	9	2 A
KB 22 P6A EU	2.200 / 2.500	500	320 - 1.610	1.200x120x40	1.100	690	613	371	220	172	197	338	195	9	2 A
Forks: max. length 1.800 mm. Add-on price per each 100 mm length increase.															
KB 28 P6B	2.800 / 3.500	500	490 - 1.820	1.200x120x45	970	690	715	470	234	228	216	383	240	20	3 A
KB 28 P6B EU	2.800 / 3.500	500	320 - 1.610	1.200x120x45	1.100	690	715	455	191	235	216	383	240	20	3 A
Forks: max. length 1.800 mm. Add-on price per each 100 mm length increase.															
KB 35 P6B	3.500 / 4.500	500	550 - 2.050	1.200x150x50	1.250	930	715	626	210	203	245	377	206	20	3 A
KB 35 P6B EU	3.500 / 4.500	500	260 - 1.510	1.200x150x50	1.150	930	715	592	216	210	245	377	206	20	3 A
Forks: max. length 1.800 mm. Add-on price per each 100 mm length increase.															
KB 40 P6B	4.000 / 5.000	500	550 - 2.050	1.200x150x60	1.250	1.115	715	625	243	233	257	375	204	20	3 A
KB 40 P6B EU	4.000 / 5.000	500	260 - 1.510	1.200x150x60	1.150	1.115	715	660	250	240	257	375	204	20	3 A
Forks: max. length 1.800 mm. Add-on price per each 100 mm length increase.															

Notes:

- One hydraulic function required.
- Q1 = capacity when clamping.
- Q2 = capacity on the forks.
- 'EU' models for Europallet handling.
- Check valve with power regeneration hydraulic circuit (for KB 10 – 22).
- Pressure relief valve.
- Forks welded to the arm carriers.
- KB-P replaces 3-13G Meyer model.

Options:

- Special openings.
- Separate sideshift.
- Integral sideshift.
- Quick change lower hooks.
- Pressure gauge.
- Load backrest.