



**Range:** 700 Kg

**Plus:**

- Suitable to handle side by side cartons and appliances such as washing machines, refrigerators televisions, etc.
- Integral sideshifting.
- Thin profile rubber faced pads allow close stacking and easy knifing into the loads.

Model	Capacity	Load Centre	Tilt Angle to Front	Chassis Width	Opening Range	Arm Width	Arm Height	Arm Length	Arm Carrier	Lost Load Centre	Horizontal Centre of Gravity	Weight	Mounting Class	Price
	<i>Q</i> kg	<i>lc</i> mm	degree	<i>A</i> mm	<i>F</i> mm	<i>K</i> mm	<i>H</i> mm	<i>L</i> mm	<i>D</i> mm	<i>C</i> mm	<i>Eh</i> mm	<i>M</i> kg	ISO 2328	€
3-2403K - a	700	935	90	1.380	610-2.450	85	1.250	660	40	112	203	546	2A	

**Notes:**

- Two hydraulic functions. Three if sideshift is required. Further hydraulic or solenoid required.
- Integral sideshift with a pressure relief valve.
- Adjustable pressure relief valve.
- Facing of the inner arms: super grip rubber.
- Including load bumper plates to protect the load.

**Options:**

- Other capacities, arm dimensions and opening ranges.
- Various facings of inner arm area.
- Separate, built-on sideshift (further additional hydraulic or solenoid required) .....
- Solenoid.....
- Solenoid valve control kit (cable drum, push botton, relay).....
- Load Backrest.
- 4 Position Relief valve.....
- 4 Position Relief valve (electrically controlled) 20-120 l/min.....
- 4 Position Relief valve (electrically controlled) 20-240 l/min.....