



**Range:** 700 Kg - 1000 Kg

**Plus:**

- Suitable to handle high volumes of cartons and appliances such as washing machines, refrigerators televisions, etc.
- 360° rotating. with both rigid arms.

06

Model	Code	Capacity	Load Centre	Chassis Width	Opening Range	Arm Width	Arm Height	Arm Length	Effective thickness	Horizontal Centre of Gravity	Weight	Mounting Class	Price
		<i>Q</i> kg	<i>BP</i> mm	<i>I</i> mm	<i>B</i> mm	<i>E</i> mm	<i>A</i> mm	<i>L</i> mm	<i>LL</i> mm	<i>HCG</i> mm	<i>W</i> kg	<i>ISO</i> 2328	
KG 07 CFOA - a	42-144	700	500	920	420-1.440	26	1.050	1.000	238	360	585	2 A	
KG 07 CFOA - b	32-134	700	500	1.020	320-1.340	26	800	800	238	280	540	2 A	
KG 07 CFOA - c	32-144	700	500	1.120	320-1.440	26	1.050	900	238	345	570	2 A	
KG 10 CFOA - a	42-144	1.000	500	920	420-1.440	26	800	800	238	435	530	2 A	

**Notes:**

- Two hydraulic functions.
- Adjustable pressure relief valve.
- Facing of the inner arms: vulcanized striped black rubber
- Including load bumper plates to protect the load.

**Options:**

- Various facings of inner arm area.
- Separate, built-on sideshift
- Solenoid
- Solenoid valve control kit (cable drum, push button, relay)
- Motor protection
- Load Backrest.
- 4 Position Relief valve.
- 4 Position Relief valve (electrically controlled) 20-120 l/min
- 4 Position Relief valve (electrically controlled) 20-240 l/min