



Range: 1000 Kg

Plus:

- Invert-a-bin attachment is used to pick up bins and containers in farming and food plants.
- 360° continuous rotation in both directions.
- When the top arm is at maximum opening the lift truck can be used as a normal forklift.

Model	Capacity in Rotation	Capacity on Forks	Load Centre	Opening Range	Width	Height	Weight	Horizontal Centre of Gravity	Thickness	Ground Clearance	Plate Length	Mounting Class
	Q kg	Q' kg	BP mm	B mm	I mm	D mm	W Kg	HCG mm	LL mm	P mm	J mm	ISO 2328
CG10S5A	1.000	2.000	575	400-700	950	781	380	230	320	9	1.200	2 A
CG10S6A	1.000	2.000	575	720-1.000	950	781	395	220	325	9	1.200	2 A
CG10S7A	1.000	2.000	575	400-1.000	950	781	480	250	350	9	1.200	2 A
CG10S8A	1.000	2.000	575	1.000-1.300	950	781	430	230	325	9	1.200	2 A

Model	Oil Flow Rate			Oil Pressure			Hydraulic Functions
	min. l/min	recom. l/min	max. l/min	min. MPa	recom. MPa	max. MPa	
CG 10 - for stabilizer	10	15	20	7.0	12.0	25.0	2
CG 10 - for rotating carriage	15	25	35	10.0	12.0	25.0	

Notes:

- Two hydraulic functions.
- Attachment is delivered without forks; the original lift truck forks can be fitted without modification.
- Q = Capacity in rotation.
- Q' = Capacity on forks.
- Please, note that the fork capacity must be adequate for load specifications.

On request:

- Separate sideshift.