



Range: 1000 Kg - 3500 Kg

Plus:

- Reduced weight, effective thickness and centre of gravity.
- Excellent visibility.
- 360° rotation in both directions.
- Used for transferring goods from production pallets to disposable ones.
- Equipped with two pairs of forks welded to the arm carriers.
- Available with side plate to stabilize the load during rotation.

Model	Capacity	Load Centre	Opening Range	Fork Dimensions	Frame Width	Minimum Carriage Width	Height	Revolving carriage Height	Weight	Horizontal Centre of Gravity	Vertical Centre of Gravity	Effective Thickness	Arm Toe-in	Side Plate Height	Fork External Width	Side Plate Distance	Ground Clearance	Mounting Class
	Q	BP	B	LxAxT	I	FL	D	D ¹	W	HCG	VCG	LL	C	M	N	R	P	ISO
	kg	mm	mm	mm	mm	mm	mm	mm	Kg	mm	mm	mm	mm	mm	mm	mm	mm	2328

With fixed side plate, fixed forks

KG E2 F4A	1.000	500	600-1.830	1.000x100x35	930	690	613	711	590	290	261	271	13	600	560	220	9	2 A
KG E3 F5A	1.400	500	650-1.980	1.100x130x40	970	690	613	711	700	349	272	285	14	600	560	220	9	2 A
KG E4 F6B	2.200	500	630-1.960	1.200x130x50	970	750	715	912	920	380	310	321	15	600	560	220	20	3 A

Without side plate, fixed forks

KG F2 F4A	1.000	500	600-1.830	1.000x100x35	930	690	613	711	510	250	257	271	13	-	560	-	9	2 A
KG F3 F5A	1.400	500	650-1.980	1.100x130x40	970	690	613	711	610	315	268	285	14	-	560	-	9	2 A
KG F4 F6B	2.200	500	630-1.960	1.200x130x50	970	750	715	912	820	348	307	321	15	-	560	-	20	3 A
KG F5 F6B	3.000	500	560-2.130	1.150x150x60	1.300	950	600	747	870	290	420	280	12	-	560	-	28	3 A
KG F6 F6B	3.500	500	560-2.130	1.150x150x60	1.300	1.100	753	801	1.080	300	450	321	12	-	560	-	15	3/4 A

Notes:

- Two hydraulic functions required.
- Models KG-EF with fixed side plate.
- Models KG-FF without side plate.
- Double check and pressure relief valve.
- Rotating center.

Options:

- Separate sideshift.
- Quick change lower hooks.
- Pressure gauge.