



Range: 4000 Kg

Plus:

- The Bolzoni Auramo rotating bale clamp model KG-GC class IV can safely transport various bales of cellulose pulp, cotton, wool and paper, etc. between the thin profile load arms (tight stacking possible)
- 360° continuous rotation in both directions.
- Slim arms for easy knifing between bale stacks.
- Reduced weight, effective thickness and center of gravity.
- Excellent visibility.

Model	Code	Capacity	Load Centre	Opening Range	Arm Dimensions	Frame Width	Weight	Horizontal Centre of Gravity	Effective Thickness	Mounting Class
		Q kg	BP mm	B mm	LxAxE mm	I mm	W Kg	HCG mm	LL mm	ISO 2328
KG 40 6G6C	44-206	4.000	600	440-2.060	1.200 x 400 x 60	1.500	1.480	340	344	4 A
KG 40 6G8C	44-206	4.000	600	440-2.060	1.500 x 400 x 60	1.500	1.650	390	344	4 A

Notes:

- Two hydraulic functions.
- Pressure relief valve.
- Wear-plates under the arms included.
- Reinforced wide gripping rods on inner arm facing.

Options:

- Special openings.
- Separate sideshift:
ISO 2328 2.....
ISO 2328 3.....
- Quick change lower hooks.
- Pressure gauge.
- Bolt-on forks and different forks lengths.
- Arms of various dimensions.
- Various facings of inner arms.
- Solenoid valve.
- Solenoid valve control kit.
- Motor and brake protection.