

Recommended Tire Size																										
Tire size	23mm	25mm	28mm	30mm	32mm	35mm	37mm [1.5"]	40mm [1.6"]	42mm [1.7"]	44mm [1.7"]	47mm [1.9"]	50mm [2.0"]	52mm [2.0"]	54mm [2.1"]	55mm [2.2"]	57mm [2.2"]	58mm [2.3"]	60mm [2.4"]	62mm [2.4"]	64mm [2.5"]	67mm [2.6"]	70mm [2.8"]	76mm [3.0"]			
Max. Tire Pressure [psi]	110		100	80		70		50			40			35			30			25						
Inside rim width, mm (ETRTO Rim Size)	ROAD, 19C/20C: Eos, Ares, Ares ES/LS, Vigor, Elan, Echelon (TC)										KEY															
	TANDEM, 19C: Tandem, Tandem Carbon (TC)										ROAD															
	TANDEM AR, 25C: Tandem Carbon AR (TC)										TANDEM															
	ALL-ROAD, 23C: Hyalite Carbon* (TC)					GRAVEL					ALL-ROAD															
	ALL-ROAD, 25C: Eos4 AR, Ares4 AR, Elan AR (TC)					GRAVEL					GRAVEL															
	GRAVEL, 22C: Hyalite CS/ES/LS (TC)					XC MTN					XC MTN															
	GRAVEL, 25C: Hyalite25 (TC)					XC MTN					XC MTN															
	GRAVEL, 25C: Hyalite Wide Carbon 29" ONLY (TSS)					XC MTN					XC MTN															
	GRAVEL, 28C: Hyalite Wide Carbon 27.5", Black Rock (TSS)					XC MTN					XC MTN															
	ALL MTN, 30/32C: Ralos30, Rage30 (TC)										ALL MTN															
ALL MTN, 30C: Black Rock, Alsea (TC & TSS)										ALL MTN																
<p>Maximum pressure: If there is a difference between our maximum recommended pressure and the tire manufacturer's recommended maximum pressure, use the lower of the two.</p> <p>TSS (hookless) models allow a max of 50 psi when using smaller tires then recommended.</p> <p>Maximum pressures are for single bikes unless otherwise noted TC: Tubeless Clincher, TSS: Tubeless Straight sidewall (AKA Hookless)</p> <p>*Rims with Hyalite Carbon name built before 2022 do not allow tires smaller then 32mm because they are designed to ETRTO 2020 specification (SN R055000 and below)</p>																										