

Recommended Tire Size																														
Tire size	23mm	25mm	28mm	32mm	35mm	37mm [1.5"]	40mm [1.6"]	42mm [1.7"]	44mm [1.7"]	47mm [1.9"]	50mm [2.0"]	52mm [2.0"]	54mm [2.1"]	55mm [2.2"]	57mm [2.2"]	58mm [2.3"]	60mm [2.4"]	62mm [2.4"]	64mm [2.5"]	67mm [2.6"]	70mm [2.8"]	76mm [3.0"]								
Max. Tire Pressure [psi]	110		100	80	70		50			40				35			30		25											
Inside rim width, mm (ETRTO Rim Size)	ROAD, 19C/20C: Eos, Ares, Ares ES/LS, Vigor, Elan, Echelon (TC)																													
	TANDEM, 19C: Tandem, Tandem Carbon (TC)																													
	GRAVEL/ALL ROAD, 22C: Hyalite, Hyalite CS, Hyalite ES/LS (TC)																													
	XC MTN, 22C: Hyalite, Hyalite CS, Hyalite ES/LS (TC)																													
	GRAVEL/ ALLROAD, 23C: Hyalite Carbon, Hyalite CS Carbon, Hyalite ES/LS Carbon (TC)																													
	XC MTN, 23C: Hyalite Carbon, Hyalite CS Carbon, Hyalite ES/LS Carbon (TC)																													
	GRAVEL/ ALLROAD, 25C: Hyalite 25 (TC)																													
	XC MTN, 25C: Hyalite25 (TC)																													
	GRAVEL/ ALLROAD, 25C: Hyalite Wide Carbon (700c) (TSS)																													
	XC MTN, 25C: Hyalite Wide Carbon (700c) (TSS)																													
	GRAVEL/ ALLROAD, 28C: Hyalite Wide Carbon (650b) (TSS)																													
	MTN, 28C: Black Rock (TSS)																													
	MTN, 30C: Ralos30, Rage30 (TC)																													
	MTN, 30C: Alsea30 (TSS)																													

TC = clincher. TSS = straight sidewall (hookless)
 Maximum pressure: If there is a difference between maximum recommended pressure and the tire manufacturer's recommended maximum pressure, use the lower of the two.
 Maximum pressures are for single bikes unless otherwise noted for tandem use
 Current Model year only. For older models, please see Tire chart under Support