



In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
PPE inspection should be conducted with the manufacturer's Instructions for Use.
Download the instructions at PETZL.COM.





CRICRI REI AV DEVICES

User information	I DEVICES	PPE information						
Surname Address		Model Serial number Year of manufacture Date of purchase	Э					
Identifier		Date of first use Manufacturer: Pet	tzl, Zl Cidex 105A - 38	920 Croll	es - Franc	ce		
Good condition (G)	To monitor (TM)	To repair (TR)	ω		N/A Not applicable			
Known product history Usage conditions or exceptional event of fall or fall arrest, use or storage at extrer modification outside manufacturer's fac	me temperatures,							
				⊘	Q,	X	⊗ ▶ 📆	N/A
 2. Preliminary observations Verify the presence and legibility of the serial number and the CE mark. Verify that the product lifetime has not been exceeded. Compare with a new device to verify there are no modifications or missing elements. 				\bigcirc	0	\circ	\bigcirc	\bigcirc
 3. Checking the moving side plate Check the condition of the moving side plate (marks, deformation, fouling, cracks, wear). If you see a hole in the side plate, retire the product. On the GRIGRI +, check the condition of the wear plate. Check the condition of the attachment hole (marks, deformation, cracks, corrosion). Check the condition of the rivets (marks, deformation, cracks, corrosion, absence of play). 				0	0	0	0	0
4. Checking the condition of the frame • Check the condition of the cam and its axle (marks, deformation, fouling, cracks, corrosion). Check the cam's mobility. • Check the condition of the friction plate (marks, deformation, fouling, cracks). • Verify the absence of foreign objects (sand) or lubricant on the rope channel. • Check the condition of the rivets (marks, deformation, cracks, corrosion, absence of play).				0	0	0	0	0
5. Checking the condition of the handle • Check the condition of the handle (marks, deformation, cracks). • Check that the handle return spring is working properly.				0	0	0	0	0
6. Checking the condition of the selector knob (GRIGRI + only) • Check the condition of the selector knob (marks, deformation, cracks). • Check the selector knob for proper function. (When rotated, the cam offers more resistance in the lead climbing position than in the top-rope position).				0	0	0	0	0
 7. Function check Do a function check with the device on the harness. Do this test with your smallest diameter rope. 								0
Comments (detail here any defects	found on the product and accomp	plished tasks)						

Inspected by

Company Date

Product fit to remain in service

Product unfit to remain in service

VERDICT

Next inspection date