

• **In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person.** Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
 • **PPE inspection should be conducted with the manufacturer's Instructions for Use.**
 Download the instructions at [PETZL.COM](https://www.petzl.com).

PROGRESS ADJUST

User information

Surname

Address

Identifier

PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France

				N/A
Good condition (G)	To monitor (TM)	To repair (TR)	Do not use, retire (R)	Not applicable

1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):

				N/A
---	---	---	---	-----

2. Preliminary observations

Verify the presence and legibility of the serial number and the CE mark.
 Verify that the product lifetime has not been exceeded.
 Compare with a new device to verify there are no modifications or missing parts.

3. Checking the condition of the rope

- Remove the connectors from the individual strands. Remove the protective sleeve from the lanyard side, and the rope clamp, in order to check the hidden areas.
- Look for wear and damage on the sheath due to use (cuts, fuzziness, chemical residues...)
- Do a tactile inspection of the core for the full length of the rope (hard spots, swelling, soft or crushed areas...)
- Check the condition of the rope at the harness attachment holes and at the ends of the lanyard.
- Check the condition of the safety stitching on all sides. Look for any threads that are loose, worn, or cut.

4. Checking the condition of the rope clamp

- Check the condition of the rope clamp (marks, wear, cracks, deformation, corrosion...).

5. Checking the condition of the connectors

- For connector inspection, see the inspection form for your connector model at Petzl.com

6. Reinstalling the connectors

- Reinstall the connectors. Verify that the connector is correctly positioned in the rope clamp.
- Verify that the plastic protective sleeve correctly positions the connector

7. Function check

- Install your lanyard on an anchor at very low height.
- Check the smoothness of length adjustment for the lanyard.
 - Verify the locking effectiveness (no slippage when you are suspended on the lanyard).

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT

Product **fit** to remain in service

Product **unfit** to remain in service

Inspected by

Company

Date

Next inspection date