



Flocculant Solvent

Product Description

Flocculant Solvent aids the removal of flocculant spillage from floors, stairs and walk ways and assists the cleaning of flocculant batching equipment as well as wetting venturi's, eductors and wetting cones.

Flocculant Solvent makes flocculant handling areas safer for plant personnel

Flocculant Solvent has been in continual use at Water Authorities, Councils & mines throughout Australia for over 15 years.

Product Features

- Liquid solution ✓
- Spray application ✓
- Suitable for most flocculant spillage problems ✓
- Fast acting ✓
- Low cost ✓

The Problem with Flocculants

Flocculants exhibit a strong affinity for water, moisture and solid surfaces. Viscous solutions form on contact with water resulting in dangerous slip hazards if spilt. The strong affinity for solid surfaces results in surface films which are difficult to remove.

The Solution

Flocculant Solvent alters the physical and chemical properties of the long chain flocculant polymer, thereby eliminating the viscosity of solutions and reversing the affinity for solid surfaces. After treatment a solid residue remains which is easily removed, resulting in a clean and safe work environment.

Where to Use Flocculant Solvent

Flocculant Solvent aids the removal of most types of spillage that occur during the storage, batching and dosing of flocculants. Apply it for cleaning ...

- storage hoppers
- metering systems
- batching systems
- floors & stairs
- eductors, wetting heads,
- wetting cones & venturi's.

Where to Use Flocculant Solvent

Flocculant Solvent is suitable for all types of flocculants

- powder flocculants
- emulsion flocculants
- dispersion flocculants
- gel flocculants

Product Range

Two types of Flocculant Solvent are available, one for anionic flocculants & one for cationic flocculants:

FS110 Flocculant Solvent

Formulated specifically for anionic flocculants. Anionic flocculants typically find application in:

- mining and minerals processing
- trade wastewater treatment
- potable water
- paper making

FS140 Flocculant Solvent

Formulated specifically for cationic & non-ionic flocculants.

These flocculants typically find application in

- mining applications
- trade wastewater treatment
- potable water
- sewage sludge dewatering
- paper making

Ordering Information

Flocculant Solvent is supplied in 20 litre polyethylene drums. Product weight is as follows:

- FS110 - 23 kg drums
- FS140 - 25 kg drums

Spray Applicators are also available to assist product application to floors, stairs and walk-ways.

The Material Safety Data Sheet is available on request. For additional information regarding this product please contact Environmental Warehouse.